

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

19.245

Point for the S 1/16 sec. cor. of secs. 22 and 23.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 22 | S 23
1991

from which

A larch, 35 ins. diam., bears S. 45° E., 26 lks. dist., mkd. S 1/16 S23 BT.

A larch, 8 ins. diam., bears N. 30° W., 26 lks. dist., mkd. S 1/16 S22 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Ascend SW. slope.

38.490

The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 5 S R 41 E
S 22 | ¼ S 23
1971

from which the remains of the original bearing trees

A fir, 37 ins. diam., bears S. 68° E., 29 lks. dist., with fragmentary scribe marks and axe marks in opened blaze. (Record, S. 71° E.)

A root hole, bears S. 70° W., 31 lks. dist., with rotten pine log alongside, 30 ins. diam., with axe marks.

and bearing trees mkd. by Albright

A fir, 13 ins. diam., bears N. 60½° E., 44 lks. dist., with healed blaze. (Record, N. 62° E.)

A fir, 16 ins. diam., bears S. 18½° W., 63 lks. dist., with healed blaze. (Record, S. 20° W.)

N. 1° 21' 00" E., beginning new measurement.

Descend NW. slope.

10.140

Point for the S-N 1/64 sec. cor. of secs. 22 and 23.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

MLG Allen

File No.

097-2013R