

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears N. 30° W., 21 lks. dist., mkd. W 1/16 S24 BT.</p> <p>The corner is located on top of a bedrock outcropping, 7 ft. x 4 ft. x 2 ft. above ground.</p>
25.50	Ravine, drains S.
30.50	Spur, slopes S.
39.020	The cor. of secs. 23, 24, 25, and 26.
	<hr/> <p>N. 0° 12' 30" E., bet. secs. 23 and 24.</p> <p>Over broken W. slope through logged area.</p>
14.00	Descend N. slope.
16.50	Descend steep NE. slope
20.205	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S 23   S 24 1991</p> </div> <p>from which</p> <p>A lodgepole pine, 10 ins. diam., bears N. 52¾° E., 94 lks. dist., mkd. S 1/16 S24 BT.</p> <p>A ponderosa pine, 20 ins. diam., bears N. 89° W., 75 lks. dist., mkd. S 1/16 S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Continue to descend steep broken NE. slope, through moderate timber and light undergrowth.</p>
40.410	<p>The ¼ sec. cor. of secs. 23 and 24, monumented with the original basalt stone, 12 x 9 x 6 ins. (record, 12 x 10 x 6 ins.), firmly set at the center of an embedded collar of stone, with illegible chisel marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E S 23   S 24 1991</p> </div> <p>from which new bearing trees</p>

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

*M. G. Allen*

File No.

098-2013R