

Dependent Resurvey of a Portion of the East Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS													
	Ascend over SW. slope, through medium timber and light undergrowth.												
19.960	<p>Point for the S 1/16 sec. cor. of sec. 24 only.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>S 1/16</td> <td> </td> <td></td> </tr> <tr> <td>S 24</td> <td> </td> <td></td> </tr> <tr> <td></td> <td> </td> <td>1991</td> </tr> </table> </div> <p>from which</p> <p>A ponderosa pine, 25 ins. diam., bears N. 82° W., 33 lks. dist., mkd. S 1/16 S24 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears N. 37° W., 27 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>	S 1/16			S 24					1991			
S 1/16													
S 24													
		1991											
22.20	Spur, slopes W.												
33.60	Gravel road, 20 lks. wide, bears irregularly E. and W.; asc. S. slope.												
35.675	From this point, a stone, 17 x 13 x 5 ins., firmly set, sides facing E. and W., projecting 8 ins. above the ground, with no marks, bears West, 0.183 chs. dist. I bury this stone in place.												
36.00	Spur, slopes SW.												
39.920	<p>The ¼ sec. cor. of sec. 24 only, monumented with the original slate stone, 18 x 14 x 5 ins. (record, 17 x 14 x 5 ins.), loosely set at the center of an ancient stone mound, no marks.</p> <p>At the corner point</p>												
<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; margin: 0;">UNION COUNTY SURVEYOR</p> <hr/> <p>Date Received <u>3/5/13</u></p> <hr/> <p>Date Filed <u>3/5/13</u></p> <hr/> <p>By <u>RT Galbreath</u></p> <hr/> <p>File No. <u>099-2013R</u></p> </div>	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 5 S</td> <td> </td> <td></td> </tr> <tr> <td>R 41 E</td> <td> </td> <td>R 42 E</td> </tr> <tr> <td>¼ S 24</td> <td> </td> <td></td> </tr> <tr> <td></td> <td> </td> <td>1991</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 20 ins. diam., bears S. 50° W., 73 lks. dist., mkd. ¼ S24 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 81° W., 39 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>	T 5 S			R 41 E		R 42 E	¼ S 24					1991
T 5 S													
R 41 E		R 42 E											
¼ S 24													
		1991											