

487

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 19   S 20 1991</p> <p>from which new bearing trees</p> <p>A larch, 12 ins. diam., bears N. 11½° E., 60 lks. dist., mkd. ¼ S20 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears N. 42° W., 9 lks. dist., mkd. ¼ S19 BT.</p>
<p>UNION COUNTY SURVEYOR</p>	<p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
<p>Date Received <u>3/5/13</u></p>	<p>The corner is located at the top of a steep SE. slope.</p>
<p>Date Filed <u>3/5/13</u></p>	<p>From the cor. of secs. 20, 21, 28, and 29.</p>
<p>By <u>W. G. Munn</u></p>	<p>S. 89° 12' 00" W., bet. secs. 20 and 29.</p>
<p>File No. <u>103-2013R</u></p>	<p>Descend W. slope along wire fence.</p>
<p>33.00</p>	<p>Stream, 5 lks. wide, course N.; asc. gradual E. slope.</p>
<p>40.030</p>	<p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 20 ¼ S 29 1992</p> <p>from which</p> <p>A lodgepole pine, 22 ins. diam., bears N. 59½° E., 118 lks. dist., mkd. ¼ S20 BT.</p> <p>A lodgepole pine, 25 ins. diam., bears S. 59° E., 70 lks. dist., mkd. ¼ S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a gradual S. slope in the S. edge of a clearing.</p>
<p>54.00</p>	<p>Continue over rolling land, through logging operation.</p> <p>Meandering stream, 4 lks. wide, course N.; asc. E. slope.</p>