
CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

80.00 The cor. of secs. 21,22,27, and 28,monumented with the original slate stone, 14 x 12 x 6 ins., loosely set at the center of the remains of an old stone mound, with 4 grooves on one face. Alongside find a water pipe, 2 ins. diam., firmly set flush with the ground, with metal washer mkd. CX 23 1973. At the corner point set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap, from which:



A ponderosa pine, 13 ins. diam., bears N.51°E., 95 lks. dist. mkd. T5S R41E S22 BT.

A ponderosa pine, 18 ins. diam., bears S.24°E., 90 lks. dist. mkd. T5S R41E S27 BT.

A ponderosa pine, 15 ins. diam., bears S.22°W., 41 lks. dist. mkd. T5S R41E S28 BT.

A ponderosa pine, 15 ins. diam., bears N.57°W., 47 lks. dist. mkd. T5S R41E S21 BT.

A corner of wire fences extending S. and E., bears S. 30° E., 0.130 chs. dist.

Deposit a white "DEEP-1" magnetic marker at the base of the water pipe within, and the corner stone alongside the stainless steel post.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 5" above ground, with a 1' mound of stone to cap from which:

A pine, 14" diam., bears N.50°50'E., 62.79', with a 22" x 3" blaze (not legible).

A pine, 17" diam., bears S.24°30'E., 59.76', with a 19" x 4" blaze (not legible).

A pine, 16" diam., bears S.21°12'W., 26.71', with a 18" x 4" blaze (not legible).

A pine, 15" diam., bears N.57°02'W., 30.26', with a 18" x 4" blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

(COUNTY OFFICIAL)

State of day	_ I hereby certify that the within inst	rument was filed in this office
Office of	County of	
File No 098-1994R		
By Styry T. Black		RONALD E STOLL 2058
Date Filed 10/23/94		OREGON JULY 15 1983
Date Received 10/18/94		M4 State 10/94
Charles Charles Annual Commission		LAND SURVEYOR
SURVIVOR		PROFESSIONAL
		RECISTERED

(DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

		1. 5 5., R. 41 E., Willamette Meridian, Oregon	
	CHAINS		
		A larch, 14 ins. diam., bears S. 6½° E., 116 lks. dist., mkd. N 1/16 S27 BT.	
		A ponderosa pine, 16 ins. diam., bears S. 21½° W., 157 lks. dist., mkd. N 1/16 S28 BT.	
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	
	60.10	Barbed wire fence, bears E. and W.	
	63.00	Graveled road, 30 lks. wide, bears N. 30° W. and S. 30° E.	
	67.00	Oregon State Highway No. 203, paved, 40 lks. wide, bears N. 40° W. and S. 40° E.; continue along broken W. slope along wire fence.	
80.000		The cor. of secs. 21, 22, 27, and 28, monumented with the original slate stone, $14 \times 12 \times 6$ ins., loosely set at the center of the remains of an old stone mound, with 4 grooves on one face. Alongside find a water pipe, 2 ins. diam., firmly set flush with the ground, with metal washer mkd. CX 23 1973.	
		At the corner point	
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.	
		T 5 S R 41 E S 21 S 22 S 28 S 27 1991	
	from which new bearing trees		
A ponderosa pine, 13 ins. diam., bears N. 51° E., 95 lks. dist., mkd. T5S R41E S22 BT.		A ponderosa pine, 13 ins. diam., bears N. 51° E., 95 lks. dist., mkd. T5S R41E S22 BT.	
	A ponderosa pine, 18 ins. diam., bears S. 24° E., 90 lks. dist., mkd. T5S R41E S27 BT.		
		A ponderosa pine, 15 ins. diam., bears S. 22° W., 41 lks. dist., mkd. T5S R41E S28 BT.	
		A ponderosa pine, 15 ins. diam., bears N. 57° W., 47 lks. dist., mkd. T5S R41E S21 BT.	
		Deposit a white "DEEP-1" magnetic marker at the base, the water pipe within, and the corner stone alongside the stainless steel post.	
		From this point, the corner of wire fences extending S. and E., bears S. 30° E., 0.130 chs. dist.	
UNION C	OUNTY		
SURVE	YOR	From the cor. of secs. 22, 23, 26, and 27.	
Date Received	3/5/13	S. 88° 59' 00" W., bet. secs. 22 and 27.	
rate Lengthen	2/1/10	Descend rocky W. slope.	
Date Filed	2/5/13		
EV /6/67	Um		
	0		

File No.