

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**


60.36 Point set for the W 1/16 sec. cor. of secs. 22 and 27. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap, from which:

A ponderosa pine, 119 ins. diam., bears N.43½°E., 42 lks. dist. mkd. W1/16 S22BT.

A ponderosa pine, 12 ins. diam., bears S.4½°E., 46 lks. dist. mkd. W1/16 S27 BT

A corner of barbed wire fences, extending N. and W., bears N.18¼°W., 0.27 chs. dist.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.



**Description of corner evidence found:**

Found a 2½" B.L.M. brass cap, 6" above ground, with a 1.5' mound of stone to cap from which:

A pine, 11" diam., bears N.43°01'E., 27.46', with a 19" x 4" blaze scribed "W1/16S22BT".

A pine, 12" diam., bears S.04°12'E., 30.42', with a 16" x 3" blaze (not legible).

**Description of monument and accessories I established to perpetuate the original location of this corner:**

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>10/18/94</u>
Date Filed	<u>10/23/94</u>
By	<u>Henry T. Blain</u>
File No.	<u>099-1994R</u>

REGISTERED <b>PROFESSIONAL LAND SURVEYOR</b>
<i>RM &amp; Stoll 10/94</i>
OREGON JULY 15 1983 <b>RONALD E. STOLL</b> 2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
1.00	Leave rocks; continue to desc. W. slope.
40.240	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 22</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math> S 27</p> <p>1991</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. <math>61^\circ</math> W., 22 lks. dist., mkd. <math>\frac{1}{4}</math> S27 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. <math>7^\circ</math> W., 24 lks. dist., mkd. <math>\frac{1}{4}</math> S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
49.75	Ravine, drains NW.
55.25	Spur, slopes NW.
60.360	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 22</p> <hr style="width: 50px; margin: 0 auto;"/> <p>W <math>\frac{1}{16}</math> S 27</p> <p>1991</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. <math>43\frac{1}{2}^\circ</math> E., 42 lks. dist., mkd. W <math>\frac{1}{16}</math> S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. <math>4\frac{1}{2}^\circ</math> E., 46 lks. dist., mkd. W <math>\frac{1}{16}</math> S27 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	From this point, the corner of barbed wire fences, extending N. and W., bears N. $18\frac{1}{4}^\circ$ W., 0.270 chs. dist.
	The cor. of secs. 21, 22, 27, and 28.
	N. $1^\circ 27' 30''$ E., bet. secs. 21 and 22.
	Descend NW. slope through medium timber and light undergrowth.

UNION COUNTY SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 108-2013R