

T5S41R17

442

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S R 41 E
S 27 | S 26
1991

from which

A larch, 10 ins. diam., bears N. 28¼° E., 22 lks. dist., mkd. ¼ S26 BT.

A larch, 11 ins. diam., bears N. 79½° W., 12 lks. dist., mkd. ¼ S27 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Descend NE. slope, through medium timber and light undergrowth.

80.700

The cor. of secs. 22, 23, 26, and 27, monumented with the original slate stone, 12 x 10 x 4 ins. (record, 14 x 12 x 6 ins.), firmly set at the center of an old stone mound, projecting 9 ins. above ground, with 3 grooves on the E. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 4½ ft. base, to top, with brass cap mkd.

T 5 S R 41 E
S 22 | S 23
S 27 | S 26
1991

from which new bearing trees

A fir, 15 ins. diam., bears N. 42° E., 120 lks. dist., mkd. T5S R41E S23 BT.

A ponderosa pine, 16 ins. diam., bears S. 55½° E., 128 lks. dist., mkd. T5S R41E S26 BT.

A larch, 11 ins. diam., bears S. 38° W., 119 lks. dist., mkd. T5S R41E S27 BT.

A larch, 15 ins. diam., bears N. 58° W., 84 lks. dist., mkd. T5S R41E S22 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.

The corner is located on a rocky W. slope.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 110-2013R