

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
15.665	<p>From this point, triangulation station "BOTTLE," established by the United States Army Corps of Engineers in 1973, bears S. 85° 35' 50" E., 7.243 chs. dist., monumented with a brass tablet, 4 ins. diam., firmly set in bedrock, with top mkd. CORPS OF ENGINEERS TRIANGULATION STATION BOTTLE 1973 WALLA WALLA DISTRICT DEPT OF THE ARMY and a triangle in the center.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 89° 15' 00" W., bet. secs. 23 and 26.</p> <p>Descend W. slope through logging slash.</p> <p>Remains of an original line tree, a sawed pine stump, 66 ins. diam., no marks.</p>
0.80	<p>At the center of the stump drive a railroad spike flush with the stump, mkd. X on the top, from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 54° 22' E., 15.15 lks. dist., with top mkd. RM AP S23 10 FT TO COR 1991 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 46° 57' 30" E., 15.15 lks. dist., with brass cap mkd. RM AP S26 10 FT TO COR 1991 and an arrow pointing to the corner. Set a white "DEEP-1" magnetic marker at the base of this reference monument.</p> <hr/> <p>S. 89° 46' 30" W., beginning new measurement.</p> <p>Descend W. slope through medium timber and light undergrowth.</p> <p>Dirt road, 15 lks. wide, bears N. 100° E. and S. 10° E.</p>
4.270	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: right; margin-right: 100px;"> S 23 E 1/16 ——— S 26 1991 </div> <p>from which</p> <p>A larch, 17 ins. diam., bears N. 35¼° E., 82 lks. dist., mkd. E 1/16 S23 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 65½° E., 111 lks. dist., mkd. E 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>MT Gilman</i>
File No.	112-2013R