433

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS		
	80.820	Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner.	
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.	
		T 5 S R 41 E S 23 S 24 S 26 S 25 1991	
		from which	
		A larch, 8 ins. diam., bears N. 3° E., 134 lks. dist., mkd. T5S R41E S24 BT.	
		A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. T5S R41E S25 BT.	
		A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T5S R41E S26 BT.	
		A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S23 BT.	
		Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.	
		From the gor, of gogs, 24 and 25 on the F. bdy, of the Tr	
		From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.	
		N. 89° 50' 30" W., bet. secs. 24 and 25.	
·		Descend SW. slope.	ř
	5.00	Dirt road, 20 lks. wide, bears NW. and SE.	
	9.00	South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.	en en face anno en
	20.105	Point for the E 1/16 sec. cor. of secs. 24 and 25.	
£	COUNTY	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
Date Received	3/5/13	$E \frac{1}{16} = \frac{s}{s} = \frac{24}{s}$	
Date Filed	3/5/13	1991	
1-11		from which	
By IWLC	1/War	A larch, 24 ins. diam., bears S. $80\frac{1}{4}^{\circ}$ E., 129 lks. dist., mkd. E 1/16 S25 BT.	
File 80. 114	-2013K	A ponderosa pine, 32 ins. diam., bears N. 85¾° W., 61 lks. dist., mkd. E 1/16 S24 BT.	
			Acceptance of the second of th
			And the state of t
			3