

T5S41R22

434

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend steep NE. slope.</p>
37.00	Rimrock, extends N. into prominent cliff, facing E.
39.20	Rimrock, 10 ft. high, bears NW. and SE.
40.210	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 24 and 25, monumented with the original unmarked basalt stone, 13 x 8 x 6 ins. (record, 13 x 9 x 7 ins.), firmly set, projecting 4 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 24</p> <hr style="width: 50px; margin: 0 auto;"/> <p><math>\frac{1}{4}</math></p> <p>S 25</p> <p>1991</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 22 ins. diam., bears N. 15° E., 26 lks. dist., mkd. <math>\frac{1}{4}</math> S24 BT.</p> <p>A Douglas fir, 15 ins. diam., bears S. 36° E., 39 lks. dist., mkd. <math>\frac{1}{4}</math> S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S. 88° 04' 30" W., beginning new measurement.</p> <p>Ascend NE. slope.</p>
1.65	Top of ascent, over rolling ridgetop through logging slash.
10.00	Descend broken W. slope.
14.00	<del>Ravine, drainage S.</del>
19.510	<p>Point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>Cemented a brass tablet, <math>3\frac{1}{4}</math> ins. diam., <math>3\frac{1}{2}</math> in. stem, in a drill hole in solid bedrock, with top mkd.</p> <div style="text-align: center;"> <p>S 24</p> <hr style="width: 50px; margin: 0 auto;"/> <p>W 1/16</p> <p>S 25</p> <p>1991</p> </div> <p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears S. 46° E., 64 lks. dist., mkd. W 1/16 S25 BT.</p>

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. G. [Signature]</i>
File No.	115-2013R

435

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears N. 30° W., 21 lks. dist., mkd. W 1/16 S24 BT.</p> <p>The corner is located on top of a bedrock outcropping, 7 ft. x 4 ft. x 2 ft. above ground.</p>
25.50	Ravine, drains S.
30.50	Spur, slopes S.
39.020	The cor. of secs. 23, 24, 25, and 26.
	<hr/> <p>N. 0° 12' 30" E., bet. secs. 23 and 24. Over broken W. slope through logged area.</p>
14.00	Descend N. slope.
16.50	Descend steep NE. slope.
20.205	Point for the S 1/16 sec. cor. of secs. 23 and 24.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">S 1/16 S 23   S 24 1991</p>
	from which
	<p>A lodgepole pine, 10 ins. diam., bears N. 52½° E., 94 lks. dist., mkd. S 1/16 S24 BT.</p>
	<p>A ponderosa pine, 20 ins. diam., bears N. 89° W., 75 lks. dist., mkd. S 1/16 S23 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Continue to descend steep broken NE. slope, through moderate timber and light undergrowth.</p>
40.410	The ¼ sec. cor. of secs. 23 and 24, monumented with the original basalt stone, 12 x 9 x 6 ins. (record, 12 x 10 x 6 ins.), firmly set at the center of an embedded collar of stone, with illegible chisel marks.
	At the corner point
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T 5 S R 41 E S 23   S 24 1991</p>
	from which new bearing trees

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>W. L. G. [Signature]</i>
File No.	115-20130R