433

## Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

Point for the cor. of secs. 23, 24, 25, and 26, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.  T 5 S R 41 E S 24 S 26 S 25 1991  from which  A larch, 8 ins. diam., bears N. 3° E., 134 lks. dist., mkd. T5S R41E S25 BT.  A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. T5S R41E S25 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T5S R41E S25 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S25 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S25 BT.  Deto Filed  Deto Filed  T - 2013 C  Point for the Cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30° W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NN. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  E 1/16  S 24  S 25  From which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks. dist., mkd. E 1/16 S24 BT.	CHAINS	
in the ground, and in a collar of stone, with brass cap mkd.  T 5 S R 41E S 23   S 24 S 26   S 25   1991  from which  A larch, 8 ins. diam., bears N. 3° E., 134 lks. dist., mkd. 75S R41E S24 BT.  A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. 75S R41E S25 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. 75S R41E S26 BT.  A larch, 11 ins. diam., bears N. 40° W., 68 lks. dist., mkd. 75S R41E S26 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. 75S R41E S26 BT.  Determined  Date Filed  Date Filed  Date Filed  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16   E 1/16   S 24   S 25   1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.	80.820	
from which  A larch, 8 ins. diam., bears N. 3° E., 134 lks. dist., mkd. T55 R41E S24 BT.  A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. T55 R41E S25 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T55 R41E S26 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T55 R41E S23 BT.  Determined 3/5/3  Determined 3/5/3  Determined 3/5/3  Determined 3/5/3  Determined 3/5/3  Determined 3/5/3  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  5.00  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16 S 24 S 25 1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 825 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		
A larch, 8 ins. diam., bears N. 3° E., 134 lks. dist., mkd. T5S R41E S24 BT.  A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. T5S R41E S25 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T5S R41E S26 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S26 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S23 BT.  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  E 1/16  S 24  E 1/16  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		<u>S 23   S 24</u> S 26   S 25
Mkd. T5S R41B S24 BT.  A larch, 10 ins. diam., bears S. 46° E., 24 lks. dist., mkd. T5S R41E S25 BT.  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T5S R41E S26 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S23 BT.  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16 S25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		from which
UNION COUNTY SURVEYOR  A larch, 11 ins. diam., bears S. 58° W., 122 lks. dist., mkd. T5S R41E S26 BT.  A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S23 BT.  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  5.00  Dirt road, 20 lks. wide, bears NW. and SE.  9.00  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		
Date Received  Date Filed  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  Prom the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		
A larch, 8 ins. diam., bears N. 40° W., 68 lks. dist., mkd. T5S R41E S23 BT.  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		
Date Filed  Date Filed  Date Filed  Date Filed  Deposit a white "DEEP-1" magnetic marker at the base and a 6 ft. steel fence post alongside the stainless steel post.  From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.  N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80¼° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85¾° W., 61 lks.	7/2/12	
N. 89° 50' 30" W., bet. secs. 24 and 25.  Descend SW. slope.  5.00  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  E 1/16  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80¼° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85¾° W., 61 lks.	3/6/12	
Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  E 1/16  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.	ev Mallun	From the cor. of secs. 24 and 25 on the E. bdy. of the Tp.
Descend SW. slope.  Dirt road, 20 lks. wide, bears NW. and SE.  South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.	Fia No 117-7013R	N. 89° 50' 30" W., bet. secs. 24 and 25.
South Fork of Catherine Creek, 20 lks. wide, course NW.; asc. NE. slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16 Sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16 Sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. diam., bears \$1.00 \text{ long.} \$2.00 \text{ long.} \$1.00	The contraction of the contracti	Descend SW. slope.
Slope.  20.105  Point for the E 1/16 sec. cor. of secs. 24 and 25.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16  S 24  S 25  1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.	5.00	Dirt road, 20 lks. wide, bears NW. and SE.
Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. $E \ 1/16 \ \frac{\text{S} \ 24}{\text{S} \ 25}$ $1991$ from which  A larch, 24 ins. diam., bears S. $80\frac{1}{4}$ ° E., 129 lks. dist., mkd. E $1/16 \ \text{S} \ 25 \ \text{BT}$ .  A ponderosa pine, 32 ins. diam., bears N. $85\frac{1}{4}$ ° W., 61 lks.	9.00	
in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.  E 1/16	20.105	Point for the E 1/16 sec. cor. of secs. 24 and 25.
E 1/16 —— S 25 1991  from which  A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		in the ground, and in a mound of stone, 3 ft. base, to top, with
A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		E 1/16 ——————————————————————————————————
A larch, 24 ins. diam., bears S. 80½° E., 129 lks. dist., mkd. E 1/16 S25 BT.  A ponderosa pine, 32 ins. diam., bears N. 85½° W., 61 lks.		from which
	N	A larch, 24 ins. diam., bears S. $80\frac{1}{4}^{\circ}$ E., 129 lks. dist.,