Dependent Resurvey of a Portion of the East Boundary, T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS A ponderosa pine, 30 ins. diam., bears S. 34° E., 88 lks. dist., with fragmentary scribe marks visible on opened apper blaze and with healed lower blaze. (Record, S. 30° E.) At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. T 5 S T 5 S R 41 E | S 19 S 30 R 42 E 1991 Deposit a white "DEEP-1" magnetic marker at the base of the stainless stee 42.630 Point for the cor. of secs. 24 and 25 only, determined at Currin's record distance from the amended cor. of secs. 24 and 25 and on a line extended from said amended corner through the original closing cor. of secs. 19 and 30, T. 5 S., R. 42 E. These remaining physical monuments are regarded as the most reliable evidence of the former position of the unidentified monument called on line by Currin and now recognized as the true corner point. The displaced original corner stone, 14 x 8 x 5 ins., with illegible marks, bears N. 9° 00' 00" E., 0.178 chs. dist., lying loose. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T 5 S T 5 S S 24 - R 42 E S 25 R 41 E | S 30 from which A fir, 18 ins. diam., bears S. $79\frac{1}{4}$ ° W., 41 lks. dist., mkd. T5S R41E S25 BT. A ponderosa pine, 12 ins. diam., bears N. 51° W., 22 lks. dist., mkd. T5S R41E S24 BT. Deposit the displaced corner stone alongside and a white "DEEP-1" magnetic marker at the base of the stainless steel post. From this point, the original closing cor. of secs. 19 and 30, T. 5 S., R. 42 E., bears S. 1° 14′ 30" E., 2.160 chs. dist. COUNTY UNION EYOR SUH From this same point, the amended cor. of secs. 24 and 25 only, bears S. 1° 14' 30" E., 3.960 chs. dist. Date Received N. 0° 30' 30" E., on the E. bdy. of sec. 24. File No.

Date Filed