

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

60.00 point for the N 1/16 sec. cor. of secs. 27 and 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

A larch, 14 ins. diam., bears S.6½°E., 116 lks. dist. mkd. N 1/16 S27 BT.

A ponderosa pine, 16 ins. diam., bears S.21½°W., 157 lks. dist. mkd. N 1/16 S 28 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.


**Description of corner evidence found:**

Found a 2½ " B.L.M. brass cap, 5" above ground from which:

A pine, 16" diam., bears S.20°58'W., 103.82', with a 15" x 3" blaze (not legible).

A tamarack, 16" diam., bears S.06°53'E., 77.02', with a 14" x 3" blaze scribed "N1/16 S27BT".

**Description of monument and accessories I established to perpetuate the original location of this corner:**



UNION COUNTY  
SURVEYOR

---

Date Received 10/18/94

Date Filed 10/23/94

By Gregory T. Blak

File No. 104-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*R. E. Stoll* 10/94

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_ day of \_\_\_\_\_, 19\_\_

\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

457

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
<p>60.50</p> <p>70.00</p> <p>79.060</p>	<p>A ponderosa pine, 22 ins. diam., bears S. 59° W., 79 lks. dist., mkd. W 1/16 S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue to ascend steep SE. slope.</p> <p>Dirt road, 20 lks. wide, bears NE. and SW.</p> <p>Broad ridge, bears NE. and SW.; desc. NW. slope.</p> <p>The cor. of secs. 27, 28, 33, and 34.</p>
<p>40.000</p>	<p>N. 0° 09' 30" E., bet. secs. 27 and 28.</p> <p>Descend steep NW. slope through medium timber and light undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with top flush with the surface, with brass cap mkd.</p>
<p>42.20</p>	<p style="text-align: center;">T 5 S R 41 E S 28   S 27 1991</p> <p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears N. 82¼° E., 85 lks. dist., mkd. ¼ S27 BT.</p> <p>A larch, 15 ins. diam., bears N. 44° W., 26 lks. dist., mkd. ¼ S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in the northerly edge of an abandoned dirt road, 20 lks. wide, bearing E. and W.</p>
<p>60.000</p>	<p>Graveled road, 35 lks. wide, bears N. 75° E. and S. 75° W.</p> <p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 28   S 27 1991</p> <p>from which</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. G. Miller</i>
File No.	170-2013R

458

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS					
	<p>A larch, 14 ins. diam., bears S. <math>6\frac{1}{2}^{\circ}</math> E., 116 lks. dist., mkd. N <math>1/16</math> S27 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears S. <math>21\frac{1}{2}^{\circ}</math> W., 157 lks. dist., mkd. N <math>1/16</math> S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>				
60.10	Barbed wire fence, bears E. and W.				
63.00	Graveled road, 30 lks. wide, bears N. $30^{\circ}$ W. and S. $30^{\circ}$ E.				
67.00	Oregon State Highway No. 203, paved, 40 lks. wide, bears N. $40^{\circ}$ W. and S. $40^{\circ}$ E.; continue along broken W. slope along wire fence.				
80.000	<p>The cor. of secs. 21, 22, 27, and 28, monumented with the original slate stone, 14 x 12 x 6 ins., loosely set at the center of the remains of an old stone mound, with 4 grooves on one face. Alongside find a water pipe, 2 ins. diam., firmly set flush with the ground, with metal washer mkd. CX 23 1973.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <table border="1" style="margin: auto;"> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td>S 28</td> <td>S 27</td> </tr> </table> <p>1991</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 13 ins. diam., bears N. <math>51^{\circ}</math> E., 95 lks. dist., mkd. T5S R41E S22 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears S. <math>24^{\circ}</math> E., 90 lks. dist., mkd. T5S R41E S27 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. <math>22^{\circ}</math> W., 41 lks. dist., mkd. T5S R41E S28 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears N. <math>57^{\circ}</math> W., 47 lks. dist., mkd. T5S R41E S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the water pipe within, and the corner stone alongside the stainless steel post.</p> <p>From this point, the corner of wire fences extending S. and E., bears S. <math>30^{\circ}</math> E., 0.130 chs. dist.</p> <hr/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>S. <math>88^{\circ} 59' 00''</math> W., bet. secs. 22 and 27.</p> <p>Descend rocky W. slope.</p>	S 21	S 22	S 28	S 27
S 21	S 22				
S 28	S 27				

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By



File No.

170-2013R