

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

History of original corner establishment:

DIAGRAM  
T 5 S R 41 E  
  
C-N 1/16  
  
S 27  
LS 2058  
1992

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

A pine, 16" diam., bears N.19°30'E., 29.44', scribed "CN1/16 S27BT".  
A tamarack, 9" diam., bears S.60°30'E., 36.62', scribed "CN1/16 S27BT".

UNION COUNTY  
SURVEYOR  
  
Date Received 10/18/94  
Date Filed 10/23/94  
By Guy T. Clark  
File No. 106-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

R E Stoll 10/94  
OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

K

S-15