

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
78.410	The cor. of secs. 25, 26, 35, and 36.
	N. 0° 03' 30" E., bet. secs. 25 and 26.
	Descend over broken NE. slope, through logging slash.
33.80	Graveled road, 20 lks. wide, bears NW. and SE.
40.410	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 5 S R 41 E S 26 S 25 1991
	from which
	A lodgepole pine, 11 ins. diam., bears N. 47° E., 74 lks. dist., mkd. ¼ S25 BT.
	A fir, 22 ins. diam., bears S. 65° W., 9 lks. dist., mkd. ¼ S26 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
46.90	Dry ravine, drains NW.; asc. SW. slope.
53.75	Spur, slopes NW.
60.615	Point for the N 1/16 sec. cor. of secs. 25 and 26.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	N 1/16 S 26 S 25 1991
	from which
	A larch, 12 ins. diam., bears S. 50° E., 6 lks. dist., mkd. N 1/16 S25 BT.
	A larch, 9 ins. diam., bears N. 77° W., 59 lks. dist., mkd. N 1/16 S26 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
62.25	Scout Creek, 20 lks. wide, course w.
62.70	Graveled road, 20 lks. wide, bears E. and W.; asc. steep S. slope.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	121-2013R