## Dependent Resurvey of a Portion of the East Boundary, T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS	
		T 5 S R 41 E   R 42 E % S 25   1991
		from which new bearing trees
		A fir, 18 ins. diam., bears N. 59° W., 8 lks. dist., mkd. 1/4 S25 BT.
		A ponderosa pine, 28 ins. diam., bears N. 31° W., 108 lks. dist., mkd. 4 S25 BT.
		Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.
		N. 1° 31′ 30" E., beginning new measurement.
		Descend steep NE. slope, through moderate timber and light undergrowth.
1	9.30	Bottom of steep descent: continue over gradual NE. slope.
2	1.315	Point for the N 1/16 sec. cor. of sec. 25 only.
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
		N 1/16   S 25   1991
		from which
		A lodgepole pine, 10 ins. diam., bears S. 22° W., 34 lks. dist., mkd. N 1/16 S25 BT.
		A spruce, 13 ins. diam., bears S. 71½° W., 18 lks. dist., mkd. N 1/16 S25 BT.
		Set a steel fence post alongside the stainless steel post.
3	4.50	South Fork of Catherine Creek, 50 lks. wide, course N. 20 W.
3	5.90	Dirt road, 25 lks. wide, bears NW. and SE., asc. SW. slope.
3	8.670	From this point, a point erroneously accepted as the cor. of secs. 24 and 25 only, by James Currin in 1898, bears East, 0.191 chs. dist., monumented with a basalt stone, 16 x 12 x 5 ins. (record,
UNION CO SURVEY	1	16 x 10 x 5 ins.), loosely set at the center of the remains of an old stone mound with no marks. I mark the stone AM and bury it in place and scatter the remains of the old stone mound.
Date Received	0.470	From this point, the original closing cor. of secs. 19 and 30, T. 5 S., R. 42 E., bears East, 0.104 chs. dist., determined at record distance from the original bearing trees:
Date Filed 3/5	13	A ponderosa pine, 30 ins. diam., bears N. 5° E., 42 lks. dist., with healed double blaze.
ex MOM	~~	
Fla No. 122-	2013R	