


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

40.29 Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate distances; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with top flush with the surface, with brass cap, from which:



A ponderosa pine, 12 ins. diam., bears N.20 1/2°E., 46 lks. dist. mkd. 1/4 S29 BT.

A douglas fir, 22 ins. diam., bears S.18 1/2°W., 81 lks. dist. mkd. 1/4 S30 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the corner of wire fences, extending E., W., and S., bears S. 5 1/2° W., 0.670 chs. dist.

Description of corner evidence found:

Found a 2 1/2 " B.L.M. brass cap, 5" above ground from which:

A pine, 13" diam., bears N.20°30'E., 30.36', scribed "S29XBT".

A fir, 22" diam., bears S.18°30'W., 53.46', scribed "S30XBT".

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 15" diam., bears S.74°30'E., 23.23', scribed "S29XBT"

A fir, 10" diam., bears S.72°15'W., 3.52', scribed "1/4 S30BT".

UNION COUNTY SURVEYOR
Date Received 10/20/94
Date Filed 10/23/94
By [Signature]
File No. 107-1294C

REGISTERED PROFESSIONAL LAND SURVEYOR
[Signature] 10/94
OREGON JULY 15 1983
RONALD E STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

L

T-5

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS							
	<p>A fir, 28 ins. diam., bears S. 27° W., 81½ lks. dist., with healed blaze.</p> <p>A lodgepole pine, 17 ins. diam., bears N. 34½° W., 69 lks. dist., with scribe marks ¼ S30 BT on open blaze.</p> <p>A steel fence post is set alongside the iron post.</p> <p>The corner is located 2 lks. S. of a barbed wire fence, extending E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 53' 30" W., beginning new measurement.</p> <p>Ascend over NE. slope, through medium timber and light undergrowth along wire fence.</p>						
7.50	Ascend steep NE. slope.						
19.815	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td style="text-align: right;">S 30</td></tr> <tr><td style="text-align: right;">W 1/16</td><td style="border-top: 1px solid black; text-align: right;">S 31</td></tr> <tr><td></td><td style="text-align: right;">1992</td></tr> </table> </div> <p>from which</p> <p>A larch, 12 ins. diam., bears S. 31½° E., 25 lks. dist., mkd. W 1/16 S31 BT.</p> <p>A larch, 17 ins. diam., bears N. 77½° W., 36 lks. dist., mkd. W 1/16 S30 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.</p>		S 30	W 1/16	S 31		1992
	S 30						
W 1/16	S 31						
	1992						
39.730	<p>The corner is located on a steep NE. slope, 5 lks. S. of a barbed wire fence, extending E. and W.</p> <p>The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0° 30' 00" E., bet. secs. 29 and 30.</p> <p>Descend NE. slope to Milk Creek; thence asc. SW. slope.</p>						
40.055	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

M. G. Dhu

File No.

12A-2013R

486

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>T 5 S R 41 E</p> <p style="margin-left: 100px;">S 30 S 29</p> <p style="margin-left: 100px;">1992</p>
	<p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 20½° E., 46 lks. dist., mkd. ¼ S29 BT.</p> <p style="margin-left: 40px;">A Douglas fir, 22 ins. diam., bears S. 18½° W., 81 lks. dist., mkd. ¼ S30 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the corner of wire fences, extending E., W., and S., bears S. 5½° W., 0.670 chs. dist.</p>
54.00	Descend N. slope through moderate timber and light undergrowth. Spur, slopes NW.; desc. steep N. slope.
68.00	Slope changes to W. slope.
80.110	Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	<p>T 5 S R 41 E</p> <p style="margin-left: 100px;">S 19 S 20</p> <p style="margin-left: 100px;">S 30 S 29</p> <p style="margin-left: 100px;">1992</p>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 50° E., 36 lks. dist., mkd. T5S R41E S20 BT.</p> <p style="margin-left: 40px;">A fir, 27 ins. diam., bears S. 39° E., 82 lks. dist., mkd. T5S R41E S29 BT.</p> <p style="margin-left: 40px;">A Douglas fir, 12 ins. diam., bears S. 62½° W., 46 lks. dist., mkd. T5S R41E S30 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 39° W., 73 lks. dist., mkd. T5S R41E S19 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 19 and 20, bears N. 1° 16' 30" W., 40.065 chs. dist., monumented with the original basalt stone, 11 x 11 x 7 ins., firmly set in an embedded collar of stone, with illegible chisel marks on the E. face.</p> <p>At the corner point</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>Neil Gillman</i>
File No.	124-2013R