

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

40.29 The 1/4 sec. cor. of secs. 28 and 29, monumented with the original slate stone, 17 x 11 x 3 ins. (record, 17 x 13 x 5 ins.), loosely set, projecting 14 ins. above ground, with illegible chisel marks on one face, from which an original bearing tree:

A fir, 26 ins. diam., bears N.25°E., 10 lks. dist. with mostly healed blaze and no marks visible in rotten center.

At the corner point set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap, from which:

A larch, 25 ins. diam., bears N.79 1/2°W., 116 1/2 lks. dist. mkd. 1/4 S29 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Description of corner evidence found:


Found a 2 1/2 " B.L.M. brass cap, 3" above ground from which:

A larch, 25" diam., bears N.79°30'W., 76.89', scribed "1/4 S29BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 19" diam., bears N.40°42'W., 38.18', scribed "1/4 S29BT".

A fir, 15" diam., bears S.18°39'W., 29.81', scribed "1/4 S29BT".



UNION COUNTY SURVEYOR
Date Received 10/18/84
Date Filed 10/23/84
By Gregory T. Black
File No. 108-1994R

REGISTERED PROFESSIONAL LAND SURVEYOR
R. E. Stoll 10/94
OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

M

T-9

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
79.35	Dirt road, 15 lks. wide, bears N. and S.
79.720	The cor. of secs. 28, 29, 32, and 33.
	<hr/> N. 0° 55' 30" E., bet. secs. 28 and 29. Descend over NW. slope through medium timber and light undergrowth.
33.75	Graveled road, 35 lks. wide, bears N. 70° E. and S. 70° W.; continue along W. slope.
40.290	<p>The ¼ sec. cor. of secs. 28 and 29, monumented with the original slate stone, 17 x 11 x 3 ins. (record, 17 x 13 x 5 ins.), loosely set, projecting 14 ins. above ground, with illegible chisel marks on one face, from which an original bearing tree:</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 25° E., 10 lks. dist., with mostly healed blaze and no marks visible in rotten center.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 29 S 28</p> <p>1991</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A larch, 25 ins. diam., bears N. 79½° W., 116½ lks. dist., mkd. ¼ S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
	N. 0° 25' 00" E., beginning new measurement.
	Along W. slope through medium timber and light undergrowth.
10.50	Descend NW. slope.
20.655	Point for the N 1/16 sec. cor. of secs. 28 and 29.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <p>N 1/16</p> <p>S 29 S 28</p> <p>1991</p> </div>
	from which
	A larch, 13 ins. diam., bears S. 31½° E., 12 lks. dist., mkd. N 1/16 S28 BT.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 125-2013R