

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM
T 5 S R 41 E

C 1/4

S 28
LS 2058
1992

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A fir, 9" diam., bears S.01°45'W., 176.64', scribed "CW1/4 S28BT".
- A fir, 12" diam., bears N.86°36'W., 124.37', scribed "CW1/4 S28BT".
- A tamarack, 15" diam., bears N.30°10'W., 52.89', scribed "C $\frac{1}{4}$ S28BT".
- A $\frac{1}{2}$ " iron pin set in a 18" diam. stump, bears N.46°33'E., 7.47', with a plastic cap marked "LS2058".

UNION COUNTY
SURVEYOR

Date Received 10/18/94

Date Filed 10/23/94

By Gregory T. Blaska

File No. 109-1994 R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

N

T-11