

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM
T 5 S R 41 E

C 1/4

S 27
LS 2058
1992

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A tamarack, 9" diam., bears N.75°04'E., 12.98', scribed "C¼S27BT".
- A fir, 9" diam., bears S.03°08'E., 6.63', scribed "C¼S27BT".
- A tamarack, 9" diam., bears S.50°49'W., 4.47', scribed "C¼S27BT".
- A tamarack, 11" diam., bears N.75°04'E., 12.98', scribed "C¼S27BT".

**UNION COUNTY
SURVEYOR**

Date Received 10/18/94
 Date Filed 10/23/94
 By [Signature]
 File No. 112-1994R

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

[Signature] 10/94
 OREGON
 JULY 15 1983
 RONALD E. STOLL
 2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

Q

T-15