

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


T-21

1/4 Section Corner of Sections 25 & 36, T.5S., R.41E., W.M.

History of original corner establishment:

The corner was originally established by **Henry M. Thatcher**, U. S. Deputy Surveyor, Contract Number 320, during **1879**. His record states: "Set Tamarack post 4 1/2 ft. long, 4 in. in dia. for 1/4 Sec. Cor. from which:

- A Black Pine 7 in. in dia. bears N 80°W, 29 lks. dist.
- A Tamarack 22 in. in dia. bears N 65°E, 29 lks. dist."



1991, Philip G. Griffin, Cadastral Surveyor, BLM, conducted a dependent resurvey in this township and monuments this corner at the proportionate distance, his record states:

"There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd." (as shown in the diagram). "From which

- A lodgepole pine, 11 ins. diam., bears N. 47° E., 74 lks. dist., mkd. 1/4 S25 BT.
- A fir, 22 ins. diam., bears S. 65° W., 9 lks. dist., mkd. 1/4 S26 BT.

Deposit a white "Deep-1" magnetic marker at the base of the stainless steel post."

Description of corner evidence found:

Found a 2 1/2" stainless steel pipe & brass cap, 6 ins. above ground, in mound of stone, marked as shown in the diagram above, from which:

BLM 1991 Bearing Trees:

- A lodgepole pine, 13 ins. diam., bears N. 47° E., 48.8 ft. dist., scribed "1/4 S25 BT" visible in partially healed blaze.
- A fir, 23 ins. diam., bears S. 65° W., 5.9 ft. dist., scribed "1/4 S26 BT" visible in partially healed blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

From the brass cap, I established the following references:

- Set a 1/2 ins. diam. by 24 ins. long, rebar, 23 ins. in the ground, bears S. 48° W., 313.6 feet distant, with brass washer mkd. LS 2211, RM 2, wire to the rebar.
- Set a 1/2 ins. diam. by 24 ins. long, rebar, 22 ins. in the ground, bears S. 75° W., 171.4 feet distant, with brass washer mkd. LS 2211, RM 1, wire to the rebar, with a collar of stone. Note: RM 1 bears N. 22° E., 178.5 feet distant from RM 2.

I hereby certify that the above corner was perpetuated by me and my crew on September 3, 1997.
Compass declination used 18 1/2° East.
See also, filed survey plat.
Witnessed by crew member: Roanna K. Ruston

WALLOWA COUNTY
 REGISTERED
 8/5/98
 8/29/98
 R. ROBINSON DEPUTY
 053-1998R

ROGER GREEN
 REGISTERED SURVEYOR
 1997-2000
 Roger Green
 REGISTERED SURVEYOR
 2001

Current registration period ends 6-30-99.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
78.410	<p>The cor. of secs. 25, 26, 35, and 36.</p> <hr/> <p>N. 0° 03' 30" E., bet. secs. 25 and 26.</p> <p>Descend over broken NE. slope, through logging slash.</p>
33.80	<p>Graveled road, 20 lks. wide, bears NW. and SE.</p>
40.410	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 26 S 25</p> <p>1991</p> </div> <p>from which</p> <p>A lodgepole pine, 11 ins. diam., bears N. 47° E., 74 lks. dist., mkd. 1/4 S25 BT.</p> <p>A fir, 22 ins. diam., bears S. 65° W., 9 lks. dist., mkd. 1/4 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
46.90	<p>Dry ravine, drains NW.; asc. SW. slope.</p>
53.75	<p>Spur, slopes NW.</p>
60.615	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S 26 S 25</p> <p>1991</p> </div> <p>from which</p> <p>A larch, 12 ins. diam., bears S. 50° E., 6 lks. dist., mkd. N 1/16 S25 BT.</p> <p>A larch, 9 ins. diam., bears N. 77° W., 59 lks. dist., mkd. N 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
62.25	<p>Scout Creek, 20 lks. wide, course W.</p>
62.70	<p>Graveled road, 20 lks. wide, bears E. and W.; asc. steep S. slope.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	128-2013R