

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

~~A fir, 28 ins. diam., bears S. 27° W., 81½ lks. dist.,
with healed blaze.~~

~~A lodgepole pine, 17 ins. diam., bears N. 34½° W., 69 lks.
dist., with scribe marks ¼ S30 BT on open blaze.~~

~~A steel fence post is set alongside the iron post.~~

~~The corner is located 2 lks. S. of a barbed wire fence, extending
E. and W.~~

~~S. 88° 53' 30" W., beginning new measurement.~~

~~Ascend over NE. slope, through medium timber and light undergrowth
along wire fence.~~

7.50

~~Ascend steep NE. slope.~~

19.815

Point for the W 1/16 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, and in a collar of stone, with brass cap mkd.

W 1/16 $\frac{S\ 30}{S\ 31}$
1992

from which

A larch, 12 ins. diam., bears S. 31½° E., 25 lks. dist., mkd.
W 1/16 S31 BT.

A larch, 17 ins. diam., bears N. 77½° W., 36 lks. dist., mkd.
W 1/16 S30 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.

The corner is located on a steep NE. slope, 5 lks. S. of a barbed
wire fence, extending E. and W.

39.730

The cor. of secs. 25, 30, 31, and 36 on the W. bdy. of the Tp.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 30' 00" E., bet. secs. 29 and 30.

Descend NE. slope to Milk Creek; thence asc. SW. slope.

40.055

Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

[Signature]

File No.

132-2013R