

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**History of original corner establishment:**

20.22 Point for the E 1/16 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2½ ins., 24 ins. in the ground, and in a collar of stone, with brass cap from which:

A ponderosa pine, 10 ins. diam., bears N.21½°E., 92½ lks. dist. mkd. E. 1/16 S30 BT.

A fir, 12 ins. diam., bears S.29½°E., 31½ lks. dist. mkd. 1/16 S31 BT.

The corner is located 11 lks. N. of barbed wire fence, extending E. and W.



**Description of corner evidence found:**

Found a 2½ " B.L.M. brass cap, 5" above ground, with a 2' mound of stone to cap from which:

A pine, 10" diam., bears N.21°06'W., 61.01 with a 14"x3" blaze, scribed " E1/16 S32 BT".

A fir, 12" diam., bears S.29°42'E., 20.78', with a 14"x3" blaze, scribed "E1/16 S31 BT".

**Description of monument and accessories I established to perpetuate the original location of this corner:**

**UNION COUNTY SURVEYOR**

---

Date Received 10/18/84

Date Filed 10/23/84

By Guyon T. Clark

File No. 115-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*R. E. Stoll 10/194*

---

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

T

V-4

484

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS							
39.975	<p>Descend over SW. slope to Milk Creek; thence asc. NE. slope.</p> <p>The cor. of secs. 29, 30, 31, and 32.</p> <hr/> <p>N. 89° 39' 00" W., bet. secs. 30 and 31.</p> <p>Ascend NE. slope along wire fence.</p>						
4.00	<p>Spur, slopes N.; desc. NW. slope.</p>						
17.50	<p>Ravine, drains N.; asc. NE. slope along wire fence.</p>						
20.215	<p>Point for the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">E 1/16</td> <td style="border-top: 1px solid black; padding-top: 5px;">S 30</td> </tr> <tr> <td></td> <td style="padding-top: 5px;">S 31</td> </tr> <tr> <td></td> <td style="padding-top: 5px;">1992</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 21½° E., 92½ lks. dist., mkd. E 1/16 S30 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 29½° E., 31½ lks. dist., mkd. E 1/16 S31 BT.</p> <p>The corner is located 11 lks. N. of a barbed wire fence, extending E. and W.</p>	E 1/16	S 30		S 31		1992
E 1/16	S 30						
	S 31						
	1992						
27.75	<p>Ascend broken NE. slope, along wire fence.</p> <p>Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.</p>						
40.430	<p>The ¼ sec. cor. of secs. 30 and 31, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 5 S R 41 E</td> <td style="border-top: 1px solid black; padding-top: 5px;">S 30</td> </tr> <tr> <td style="padding-right: 10px;">¼</td> <td style="padding-top: 5px;">S 31</td> </tr> <tr> <td></td> <td style="padding-top: 5px;">1971</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A larch stump, 20 ins. diam., bears N. 40° E., 13 lks. dist., with larch log alongside, with scribe marks BT legible on open blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 45° E., 16 lks. dist., with rotten remains of a larch log alongside, no marks. (Record, S. 42° E.)</p> <p>and bearing trees mkd. by Albright</p>	T 5 S R 41 E	S 30	¼	S 31		1971
T 5 S R 41 E	S 30						
¼	S 31						
	1971						

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>RLG</i>
File No.	134-2013 R