


CERTIFIED RECORD OF LAND CORNER MONUMENTATION



History of original corner establishment:

40.03 The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam. firmly set, projecting 6 ins. above ground, with brass cap, from which:

- A root hole, bears N.12°E., 30 lks. dist.
- A loose piece of pine wood with scribe marks BT, bears S. 68° E., 22 lks. dist.
- A ponderosa pine, 21 ins. diam., bears S.21°W., 14 lks. dist., no marks. (record, S.19°W.)
- A ponderosa pine, 40 ins. diam., bears S.21°W., 14 lks. dist., no marks, ins. diam., bears S. 21° W., 14 lks. dist. with healed blaze.
- A lodge pole pine, 14 ins. diam., bears N.53½°E., 168 lks. dist. mkd. T5S R41E S29BT on an open blaze. (record, N.55½°E., lks.)
- A larch, 11 ins. diam., bears S.61½°E., 68 lks. dist. mkd. T5S R41E S32 BT on open blaze. (record, S. 60 3/4° E.)
- A fir, 20 ins. diam., bears S.40½°W., 56 lks. dist. with fragmentary scribe marks visible on pitched over blaze. (record S. 42½° W.)
- A fir, 23 ins. diam., bears N.71½°W., 120½ lks. dist. with healed blaze. (record, N. 69½°W.)

A steel fence post is set alongside the iron post.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 8" above ground, from which:

- A fir, 20" diam., bears N.71°13'W., 79.51', with a 20" blaze.
- A pine, 36" diam., bears N.85°03'W., 12.8', with a blaze.
- A fir, 18" diam., bears S.40°43'W., 36.92', with a 16" blaze.
- A tamarack, 9" diam., bears S.61°31'E., 44.6', with a 20 " blaze, scribed "T5S R41E S32BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY SURVEYOR	
Date Received	<u>10/18/84</u>
Date Filed	<u>10/23/84</u>
By	<u>[Signature]</u>
File No.	<u>116-1994R</u>

REGISTERED PROFESSIONAL LAND SURVEYOR
<u>[Signature]</u> 10/94
OREGON JULY 15 1983 RONALD E. STOLL 2058


Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

V-5 T5S R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON Post 28" Long Set 24" in Ground
with 5' steel Fence Post Along side



ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

- A LP. Pine 12" BRS. N55 1/2° E 165 LKS MKD. T5S R41E S29 BT
- A W. Larch 7" BRS. S60 3/4° E 68 LKS MKD. T5S R41E S32 BT
- A Fir 15" BRS S42 1/4° W 56 LKS MKD. T5S R41E S31 BT
- A W. Fir 16" BRS N69 1/2° W 120 1/2 LKS MKD T5S R41E S30 BT

Work Done By S. ALBRIGHT Title CADASTRAL SURVEY 402 Date 9/23/71 State Registration No. RLM or Agency

Certified Cor. Record Prepared? Yes No Filed At: Date

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor.

**UNION COUNTY
SURVEYOR**

Date Received _____

Date Filed 12-28-87

By G. LANGLITZ, Deputy

File No. 433-87 R

V-5

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 41 E

$\frac{1}{4}$
S 8 | S 9
1971

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears S. 75° E.,
52½ lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A ponderosa pine, 10 ins. diam., bears N. 41¾° W.,
96 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Set 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, determined at record
bearing and distance from the original bearing trees:

A root hole, bears S. 62° E., 26 lks. dist., with
a down fir alongside, 12 ins. diam., with scribe
marks $\frac{1}{4}$ S BT visible on open blaze.

A root hole, bears S. 15° W., 32 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 41 E

$\frac{1}{4}$
S 31 | S 32
1971

from which new bearing trees

A white fir, 18 ins. diam., bears N. 40° E., 57
lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A white fir, 12 ins. diam., bears N. 43° W., 89
lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Set 5 ft. steel fence post alongside iron post.

The cor. of secs. 29, 30, 31, and 32, determined at
record bearing and distance from the remaining original
bearing trees:

A ponderosa pine, 18 ins. diam., bears S. 19° W.,
14 lks. dist., no marks visible.

A ponderosa pine, 31 ins. diam., bears N. 89¾° W.,
19 lks. dist., with scribe mark T visible on
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 41 E

S 30 | S 29
S 31 | S 32
1971

from which new bearing trees

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By N. L. G. [Signature]

File No. 015-2013R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

- A lodgepole pine, 12 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 165 lks. dist., mkd. T5S R41E S29 BT.
 - A western larch, 7 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. T5S R41E S32 BT.
 - A fir, 15 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ W., 56 lks. dist., mkd. T5S R41E S31 BT.
 - A white fir, 16 ins. diam., bears N. $69\frac{1}{2}^{\circ}$ W., 120 $\frac{1}{2}$ lks. dist., mkd. T5S R41E S30 BT.
- Set 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with the original basalt stone, 19 x 11 x 7 ins., loosely set 6 ins. in the ground, marked $\frac{1}{4}$ on E. face, from which the original bearing trees:

- A root hole, bears N. 48° E., 30 lks. dist., with a down fir alongside, 20 ins. diam., with scribe marks 4 BT visible on bark.
- A fir, 26 ins. diam., bears S. 30° W., 32 lks. dist., with scribe marks 1 T visible on bark.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E
 S 29
 S 32
 1971

from which new bearing trees

- A white fir, 10 ins. diam., bears N. 40° E., 44 lks. dist., mkd. $\frac{1}{4}$ S29 BT.
- A white fir, 14 ins. diam., bears S. 45° W., 48 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, determined at record bearing and distance from the original bearing trees:

- A western larch snag, 20 ins. diam., bears N. 40° E., 13 lks. dist., with scribe marks BT visible on opened blaze.
- A root hole, bears S. 42° E., 16 lks. dist., with a down western larch alongside, 26 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	015-2013R

482

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS		
	<p>A steel fence post is set alongside the iron post.</p> <p>N. 0° 06' 30" E., beginning new measurement.</p> <p>Descend over gradual NE. slope through dead timber.</p>	
4.20	<p>Ravine, drains S. 70° E.; asc. S. slope.</p>	
16.00	<p>Ridge, bears E. and W.; desc. N. slope.</p>	
20.015	<p>Point for the N 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>	
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/17</u></p> <p>By <u>ADG</u></p> <p>File No. <u>135-2013R</u></p>	<p style="text-align: center;">N 1/16 S 31 S 32 1992</p> <p>from which</p> <p>A fir, 17 ins. diam., bears N. 28° E., 80 lks. dist., mkd. N 1/16 S32 BT.</p> <p>A fir, 17 ins. diam., bears N. 55° W., 36 lks. dist., mkd. N 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>	
	33.00	<p>Descend NE. slope.</p>
	40.030	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 30 S 29 S 31 S 32 1971</p> <p>from which the remains of the original bearing trees</p> <p>A root hole, bears N. 12° E., 30 lks. dist.</p> <p>A loose piece of pine wood with scribe marks BT, bears S. 68° E., 22 lks. dist.</p> <p>A ponderosa pine, 21 ins. diam., bears S. 21° W., 14 lks. dist., no marks. (Record, S. 19° W.)</p> <p>A ponderosa pine, 40 ins. diam., bears N. 89½° W., 19 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Albright</p> <p>A lodgepole pine, 14 ins. diam., bears N. 53½° E., 168 lks. dist., mkd. T5S R41E S29 BT on open blaze. (Record, N. 55½° E., 165 lks.)</p>

483

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A larch, 11 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ E., 68 lks. dist.,
mkd. T5S R41E S32 BT on open blaze. (Record, S. $60\frac{3}{4}^{\circ}$ E.)

A fir, 20 ins. diam., bears S. $40\frac{1}{2}^{\circ}$ W., 56 lks. dist.,
with fragmentary scribe marks visible on pitched over
blaze. (Record, S. $42\frac{1}{4}^{\circ}$ W.)

A fir, 23 ins. diam., bears N. $71\frac{1}{4}^{\circ}$ W., $120\frac{1}{2}$ lks. dist.,
with healed blaze. (Record, N. $69\frac{1}{2}^{\circ}$ W.)

A steel fence post is set alongside the iron post.

From the cor. of secs. 28, 29, 32, and 33.

S. $89^{\circ} 07' 00''$ W., bet. secs. 29 and 32.

Over rolling land, through recently logged area.

0.30

Center of graveled road, 25 lks. wide, bears N. 35° W. and
S. 35° E.

39.820

The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with an iron post,
 $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with
brass cap mkd.

T 5 S R 41 E
S 29
 $\frac{1}{4}$ ———
S 32
1971

from which the remains of the original bearing trees

A root hole, bears N. 48° E., 30 lks. dist., with
uprooted fir alongside, 20 ins. diam., no marks.

A sawed fir stump, 26 ins. diam., bears S. 30° W.,
 $33\frac{1}{2}$ lks. dist., no marks. (Record, 32 lks.)

and bearing trees mkd. by Albright

A fir, 17 ins. diam., bears N. 40° E., 44 lks. dist.,
with scribe marks BT visible on partially healed blaze.

A fir, 19 ins. diam., bears S. $43\frac{3}{4}^{\circ}$ W., 49 lks. dist.,
with healed blaze. (Record, S. 45° W., 48 lks.)

and new bearing trees

A larch, 12 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 17 lks. dist.,
mkd. $\frac{1}{4}$ S32 BT.

A larch, 9 ins. diam., bears N. $83\frac{3}{4}^{\circ}$ W., 30 lks. dist.,
mkd. $\frac{1}{4}$ S29 BT.

A steel fence post is set alongside the iron post.

N. $88^{\circ} 34' 00''$ W., beginning new measurement.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

File No.

135-2013R