


CERTIFIED RECORD OF LAND CORNER MONUMENTATION



History of original corner establishment:

39.82 The 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap, from which:

Original bearing trees:

A roothole, bears N.48°E., 30 lks. dist., with uprooted fir alongside, 20 ins. diam., no marks.
A sawed fir stump, 26 ins. diam., bears N.40°E., 44 lks. dist. no marks. (record, 32 lks.)

Bearing trees marked by Albright:

A fir, 17 ins. diam., bears N.40°E., 44 lks. dist. with scribe marks BT visible on partially healed blaze.
A fir, 19 ins. diam., bears S.43 3/4°W., 49 lks. dist. with healed blaze. (record, S.45°W., 48 lks.)

New bearing trees:

A larch, 12 ins. diam., bears S.59 1/2°W., 17 lks. dist. mkd. 1/4 S32 BT.
A larch, 9 ins. diam., bears N.83 3/4°W., 30 lks. dist. mkd. 1/4 S29 BT.
A steel fence post is set alongside the iron post.

Description of corner evidence found:

Found a 2 1/2" B.L.M brass cap, 6" above ground, with a 2' mound of stone to cap, from which:

A fir, 14" diam., bears N.39°56'E., 28.87', dead with a 13" x 4" blaze (not legible).
A fir, 14" diam., bears S.01°22'E., 30.57', with a scar over blaze.
A fir, 16" diam., bears S.43°33'W., 31.73', with a 18" healed blaze.
A tamarack, 11" diam., bears S.59°19'W., 11.18', with a 18" x 4" blaze scribed " 1/4 S32BT".
A tamarack, 8" diam., bears N.83°03'W., 19.43', with a 18" x 4" blaze, scribed " 1/4 S29BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY SURVEYOR
Date Received 10/18/94
Date Filed 10/23/94
By Guy T. Clark
File No. 117-1994R

REGISTERED PROFESSIONAL LAND SURVEYOR
RJ & State 10/94
OREGON JULY 15 1983
RONALD E STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

V

V-7

V-7 T55 R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON POST 28" Long Set 22" IN GROUND
with 5' steel Fence post Along side
Deposit OR 19.5 TONE Along side IRON post

T55 R41E BRASS
1/4 S29 CAP
4 S32 MKD
1971

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A W. Fir 10" BRS. N40E 44 LKS MKD 1/4 S29 BT
A W. Fir 14" BRS. S45°W 48 LKS MKD 1/4 S32 BT

Work Done By S ALBRIGHT Title CADSTRAL SURVEYOR Date 9/23/71 State Registration No. RL 5 704 or Agency B/M
Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor.

UNION COUNTY SURVEYOR	
By Received _____	
Date Filed <u>12-28-87</u>	
By <u>G. LANGUITZ, DEPUTY</u>	
File No. <u>434-87R</u>	

V-7

79
T5S 41 N07

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

- A lodgepole pine, 12 ins. diam., bears N. 55½° E., 165 lks. dist., mkd. T5S R41E S29 BT.
 - A western larch, 7 ins. diam., bears S. 60¾° E., 68 lks. dist., mkd. T5S R41E S32 BT.
 - A fir, 15 ins. diam., bears S. 42¼° W., 56 lks. dist., mkd. T5S R41E S31 BT.
 - A white fir, 16 ins. diam., bears N. 69½° W., 120½ lks. dist., mkd. T5S R41E S30 BT.
- Set 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 29 and 32, monumented with the original basalt stone, 19 x 11 x 7 ins., loosely set 6 ins. in the ground, marked ¼ on E. face, from which the original bearing trees:

- A root hole, bears N. 48° E., 30 lks. dist., with a down fir alongside, 20 ins. diam., with scribe marks 4 BT visible on bark.
- A fir, 26 ins. diam., bears S. 30° W., 32 lks. dist., with scribe marks 1 T visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E
 ¼ S 29
 S 32
 1971

from which new bearing trees

- A white fir, 10 ins. diam., bears N. 40° E., 44 lks. dist., mkd. ¼ S29 BT.
- A white fir, 14 ins. diam., bears S. 45° W., 48 lks. dist., mkd. ¼ S32 BT.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 30 and 31, determined at record bearing and distance from the original bearing trees:

- A western larch snag, 20 ins. diam., bears N. 40° E., 13 lks. dist., with scribe marks BT visible on opened blaze.
- A root hole, bears S. 42° E., 16 lks. dist., with a down western larch alongside, 26 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By Nick G. Munn

File No. 016-2013R

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>A larch, 11 ins. diam., bears S. 61$\frac{1}{4}$$^{\circ}$ E., 68 lks. dist., mkd. T5S R41E S32 BT on open blaze. (Record, S. 60$\frac{3}{4}$$^{\circ}$ E.)</p> <p>A fir, 20 ins. diam., bears S. 40$\frac{1}{2}$$^{\circ}$ W., 56 lks. dist., with fragmentary scribe marks visible on pitched over blaze. (Record, S. 42$\frac{1}{4}$$^{\circ}$ W.)</p> <p>A fir, 23 ins. diam., bears N. 71$\frac{1}{4}$$^{\circ}$ W., 120$\frac{1}{2}$ lks. dist., with healed blaze. (Record, N. 69$\frac{1}{2}$$^{\circ}$ W.)</p> <p>A steel fence post is set alongside the iron post.</p>
UNION COUNTY SURVEYOR	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>S. 89$^{\circ}$ 07' 00" W., bet. secs. 29 and 32.</p> <p>Over rolling land, through recently logged area.</p>
Date Received <u>3/5/13</u>	
Date Filed <u>3/5/13</u>	
By <u>[Signature]</u>	
File No. <u>136-2013R</u>	
0.30	Center of graveled road, 25 lks. wide, bears N. 35 $^{\circ}$ W. and S. 35 $^{\circ}$ E.
39.820	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 29 $\frac{1}{4}$ ————— S 32 1971</p> <p>from which the remains of the original bearing trees</p> <p>A root hole, bears N. 48$^{\circ}$ E., 30 lks. dist., with uprooted fir alongside, 20 ins. diam., no marks.</p> <p>A sawed fir stump, 26 ins. diam., bears S. 30$^{\circ}$ W., 33$\frac{1}{2}$ lks. dist., no marks. (Record, 32 lks.)</p> <p>and bearing trees mkd. by Albright</p> <p>A fir, 17 ins. diam., bears N. 40$^{\circ}$ E., 44 lks. dist., with scribe marks BT visible on partially healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 43$\frac{3}{4}$$^{\circ}$ W., 49 lks. dist., with healed blaze. (Record, S. 45$^{\circ}$ W., 48 lks.)</p> <p>and new bearing trees</p> <p>A larch, 12 ins. diam., bears S. 59$\frac{1}{2}$$^{\circ}$ W., 17 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p> <p>A larch, 9 ins. diam., bears N. 83$\frac{3}{4}$$^{\circ}$ W., 30 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>A steel fence post is set alongside the iron post.</p>
	N. 88 $^{\circ}$ 34' 00" W., beginning new measurement.