

V-9


LAND CORNER RECORD
(Rectangular)

V-9

5680-2

1. T. 5 S. R. 41 E. No. V-9 Cor. SEC. Mer. Will State DC N. F. 10 W Dist. UNION

2. Corner Status



3. Original Description _____ Vol. _____ Page _____ Where Recorded _____

4. Description of Corners: POST 10"
8" 8°N40'E 10 lbs
" 8"N 5°W 14 lbs
" 5" S 33° W
4" S 15° E 17 lbs

5. Investigation Notes: WOODEN POST 2" BY 6" LAYING ON GROUND
FOREST SERVICE BOUNDARY SIGN NAILED ON SQUARE
SIDE
A PIECE OF WOOD 20" X 7 FT WITH B.T.
SCRIBED ON IT.
A PIECE OF SIGN 4" BY 6" WITH
B.T. SCRIBED ON IT.
USE PHOTO ENW-9-45. THIS LARGE M.D.W. HAS
AN OLD FRAZIER ROCK LOOK OUT SIGN NAILED
ON AN 18" W.D. TAKE RD AT NORTH END OF M.D.W.
FOLLOW RD. TO F.S. LOCATION POSTER. ON LEFT
HAND SIDE OF RD. THIS IS SEC. COR. AND
MARKED WITH YELLOW RIBBON.

Photo Identification
 Photo No. ENW-9-45
 Taken By: PIN PUNCHED

Plane Coordinate Position Data
 State _____ Zone _____

Map By _____
 Field Book No. _____
 Where Filed _____

Evaluation
 Monument _____
 Survey _____

Land Status _____

6. Signed E. A. [Signature] Title _____ Date 10/28/66

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-28-87

By G. LANGLITZ, DEPUTY


File No. 435-87R

V-9

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

80.58 Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distances; the true corner point cannot be determined from the remains of the original evidence, a sketched blaze from one of the original bearing trees with the scribe marks BT legible. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground with top flush with the ground, with brass cap, from which:



- A lodgepole pine, 12 ins. diam., bears N.45½°E., 136 lks. dist. mkd. T5S R41E S28 BT.
- A lodgepole pine, 15 ins. diam., bears S.58 3/4°E., 298 lks. dist. mkd. T5S R41E S33 BT.
- A lodgepole pine, 6 ins. diam., bears S.49¼°W., 367 lks. dist. mkd. X at breast height and BT at the base.
- A fir, 20 ins. diam., bears N.50°W., 431 lks. dist. mkd. T5S R41E S29 BT.

Deposit a white "DEEP-1" magnetic marker at the base, the remains of the original bearing tree alongside and set two 6 ft. steel fence posts alongside the stainless steel post.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 2" above ground, with a 2" mound of stone to cap from which:

- A fir, 16" diam., bears S.58°E., 196.73', with a 19" x 4" blaze, scribed "T5S R41E S33 BT".
- A fir, 17" diam., bears N.50°W., 284.52', with a 16" x 4" blaze, scribed "T5S R41E S29 BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

- A fir, 12" diam., bears N.08°E., 196.73', with a 16" x 4" blaze, scribed "T5S R41E S28 BT".
- A tamarack, 12" diam., bears S.62°W., 191.17', with a 19" x 4" blaze, scribed "T5S R41E S32 BT".

UNION COUNTY SURVEYOR

Date Received 10/20/94

Date Filed 10/23/94

By [Signature]

File No. 118-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature] 10/94
OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
40.290	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 32 S 33 1991</p> <p>from which</p> <p>A lodgepole pine, 9 ins. diam., bears S. 21¼° E., 78 lks. dist., mkd. ¼ S33 BT.</p> <p>A lodgepole pine, 11 ins. diam., bears S. 77° W., 13 lks. dist., mkd. ¼ S32 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p> <p>Continue along W. slope through logged area.</p>
43.10	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.
80.10	Graveled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
80.580	<p>Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; the true corner point cannot be determined from the remains of the original evidence, a detached blaze from one of the original bearing trees with the scribe marks BT legible.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground with top flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 29 S 28 S 32 S 33 1991</p> <p>from which new bearing trees</p> <p>A lodgepole pine, 12 ins. diam., bears N. 45½° E., 136 lks. dist., mkd. T5S R41E S28 BT.</p> <p>A lodgepole pine, 15 ins. diam., bears S. 58¾° E., 298 lks. dist., mkd. T5S R41E S33 BT.</p> <p>A lodgepole pine, 6 ins. diam., bears S. 49¼° W., 367 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A fir, 20 ins. diam., bears N. 50° W., 431 lks. dist., mkd. T5S R41E S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the remains of the original bearing tree alongside and set two 6 ft. steel fence posts alongside the stainless steel post.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	137-2013R