

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89° 14' 00" W., bet. secs. 28 and 33.</p> <p>Descend NW. slope.</p>
19.50	Top of steep E. slope.
19.930	<p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: right; margin-right: 100px;"> <p>S 28 E 1/16 ——— S 33 1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 26 ins. diam., bears N. 22° E., 18 lks. dist., mkd. E 1/16 S28 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 63° E., 43 lks. dist., mkd. E 1/16 S33 BT.</p>
	<p>Along gradual S. slope.</p>
24.00	Ascend SE. slope.
39.75	Barbed wire fence, bears N. and S.
39.860	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: right; margin-right: 100px;"> <p>T 5 S R 41 E S 28 ¼ ——— S 33 1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears S. 28¾° W., 45 lks. dist., mkd. ¼ S33 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 44° W., 84 lks. dist., mkd. ¼ S28 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	Ascend SE. slope through logged area.
41.50	Dirt road, 20 lks. wide, bears NE. and SW.
55.00	Descend W. slope.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>MLB</i>
File No.	134-2013R