

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A larch, 10 ins. diam., bears S. 50° E., 20 lks. dist., mkd. E 1/16 S34 BT.</p> <p>A ponderosa pine, 24 ins. diam., bears N. 78½° W., 107 lks. dist., mkd. E 1/16 S27 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend W. slope along old fence line.</p>
21.25	Ravine, drains SW.; asc. over broken SE. slope.
37.75	Dirt road, 20 lks. wide, bears N. 30° E. AND S. 30° W.
39.530	<p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 27 ¼ S 34 1991</p> <p>from which</p> <p>A ponderosa pine, 20 ins. diam., bears N. 33° E., 45 lks. dist., mkd. ¼ S27 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears S. 77° W., 44 lks. dist., mkd. ¼ S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a monument of unknown origin, bears N. 69° 06' 50" W., 1.022 chs. dist., a stone, 10 x 8 x 5 ins., in the center of a recently made stone mound and plainly mkd. ¼ S. Evidence is not in accord with the observed pattern or condition of the original survey and is not regarded as evidence of the original corner position.</p> <p>Ascend steep SE. slope.</p>
59.295	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 27 W 1/16 ——— S 34 1991</p> <p>from which</p> <p>A ponderosa pine, 13 ins. diam., bears N. 53° E., 65 lks. dist., mkd. W 1/16 S27 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>MLG/ML</i>
File No.	141-2013R

457

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 22 ins. diam., bears S. 59° W., 79 lks. dist., mkd. W 1/16 S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Continue to ascend steep SE. slope.</p>
60.50	<p>Dirt road, 20 lks. wide, bears NE. and SW.</p>
70.00	<p>Broad ridge, bears NE. and SW.; desc. NW. slope.</p>
79.060	<p>The cor. of secs. 27, 28, 33, and 34.</p> <hr/> <p>N. 0° 09' 30" E., bet. secs. 27 and 28.</p> <p>Descend steep NW. slope through medium timber and light undergrowth.</p>
40.000	<p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with top flush with the surface, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 28 S 27</p> <p>1991</p> </div> <p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears N. 82½° E., 85 lks. dist., mkd. ¼ S27 BT.</p> <p>A larch, 15 ins. diam., bears N. 44° W., 26 lks. dist., mkd. ¼ S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in the northerly edge of an abandoned dirt road, 20 lks. wide, bearing E. and W.</p>
42.20	<p>Graveled road, 35 lks. wide, bears N. 75° E. and S. 75° W.</p>
60.000	<p>Point for the N 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S 28 S 27</p> <p>1991</p> </div> <p>from which</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. G. Khan</i>
File No.	141-2013R