

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS 19.00	Track road, 20 lks. wide, bears E. and W.																
22.00	Broad ridge, bears NE. and SW.; desc. gradual NW. slope.																
40.310	The cor. of secs. 27, 28, 33, and 34, monumented with the original slate stone, 12 x 8 x 6 ins. (record 12 x 10 x 8 ins.), firmly set in an embedded collar of stone, mkd. with 2 grooves on the E. and W. faces, 5 grooves on the N. face, and 1 groove on the S. face. At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="4" style="text-align: center;">T 5 S R 41 E</td></tr> <tr><td style="text-align: center;">S 28</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">S 27</td><td></td></tr> <tr><td style="text-align: center;">S 33</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">S 34</td><td></td></tr> <tr><td colspan="4" style="text-align: center;">1991</td></tr> </table> from which new bearing trees A larch, 16 ins. diam., bears N. 9° E., 165 lks. dist., mkd. X at breast height and BT at the base. A Douglas fir, 18 ins. diam., bears N. 27¼° E., 99½ lks. dist., mkd. T5S R41E S27 BT. A larch, 15 ins. diam., bears S. 83° E., 145 lks. dist., mkd. T5S R41E S34 BT. A Douglas fir, 14 ins. diam., bears S. 36° W., 76 lks. dist., mkd. T5S R41E S33 BT. There is no suitable tree available in sec. 28. Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post. <hr/> From the cor. of secs. 26, 27, 34, and 35. S. 89° 29' 30" W., bet. secs. 27 and 34. Descend over W. slope through medium timber and light undergrowth.	T 5 S R 41 E				S 28		S 27		S 33		S 34		1991			
T 5 S R 41 E																	
S 28		S 27															
S 33		S 34															
1991																	
7.00	Oil surfaced road, 25 lks. wide, bears N. 30° W. and S. 30° E.																
19.00	Oregon State Highway No. 203, paved, 40 lks. wide, bears N. 30° E. and S., in a curve.																
19.765	Point for the E 1/16 sec. cor. of secs. 27 and 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="2"></td><td style="text-align: center;">S 27</td><td colspan="2"></td></tr> <tr><td style="text-align: center;">E 1/16</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td style="text-align: center;">S 34</td><td colspan="2"></td></tr> <tr><td colspan="5" style="text-align: center;">1991</td></tr> </table> from which			S 27			E 1/16		S 34			1991					
		S 27															
E 1/16		S 34															
1991																	

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>W. L. G. Man</i>
File No.	143-201312

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A larch, 10 ins. diam., bears S. 50° E., 20 lks. dist., mkd. E 1/16 S34 BT.</p> <p>A ponderosa pine, 24 ins. diam., bears N. 78½° W., 107 lks. dist., mkd. E 1/16 S27 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Descend W. slope along old fence line.</p>
21.25	<p>Ravine, drains SW.; asc. over broken SE. slope.</p>
37.75	<p>Dirt road, 20 lks. wide, bears N. 30° E. AND S. 30° W.</p>
39.530	<p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p>S 27</p> <p>¼ ———</p> <p>S 34</p> <p>1991</p> </div> <p>from which</p>
	<p>A ponderosa pine, 20 ins. diam., bears N. 33° E., 45 lks. dist., mkd. ¼ S27 BT.</p>
	<p>A ponderosa pine, 16 ins. diam., bears S. 77° W., 44 lks. dist., mkd. ¼ S34 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>From this point, a monument of unknown origin, bears N. 69° 06' 50" W., 1.022 chs. dist., a stone, 10 x 8 x 5 ins., in the center of a recently made stone mound and plainly mkd. ¼ S. Evidence is not in accord with the observed pattern or condition of the original survey and is not regarded as evidence of the original corner position.</p>
	<p>Ascend steep SE. slope.</p>
59.295	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>S 27</p> <p>W 1/16 ———</p> <p>S 34</p> <p>1991</p> </div>
	<p>from which</p>
	<p>A ponderosa pine, 13 ins. diam., bears N. 53° E., 65 lks. dist., mkd. W 1/16 S27 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	ML G Miller
File No.	143-2013R