

# CERTIFIED RECORD OF LAND CORNER MONUMENTATION


## History of original corner establishment:

20.66 Point set for the N 1/16 sec. cor. of secs. 31 and 32. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap, from which:

A fir, 17 ins. diam., bears N.28°E., 80 lks. dist. mkd. N 1/16 S32 BT.

A Fir, 17 ins. diam., bears N.55°W., 36 lks. dist. mkd. N 1/16 S31 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.



## Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 4" above ground with a 2' mound of stone to cap, from which:

A fir, 16" diam., bears N.28°08'E., 52.70', with a 16" blaze, scribed "N1/16 S32 BT".

A fir, 17" diam., bears N.55°36'W., 23.82', with a 17" blaze, scribed "N1/16 S31 BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY  
SURVEYOR

Date Received 10/20/94

Date Filed 10/23/94

By Gregory L. Black

File No. 122-6994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

RW & Stoll 10/94

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_ day of \_\_\_\_\_, 19 \_\_\_\_  
\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

482

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

| CHAINS       |   |              |  |      |      |      |      |      |  |
|--------------|---|--------------|--|------|------|------|------|------|--|
|              | A steel fence post is set alongside the iron post.<br><hr style="width: 20%; margin: 0 auto;"/>   |              |  |      |      |      |      |      |  |
|              | N. 0° 06' 30" E., beginning new measurement.  |              |  |      |      |      |      |      |  |
|              | Descend over gradual NE. slope through dead timber.   |              |  |      |      |      |      |      |  |
| 4.20         | Ravine, drains S. 70° E.; asc. S. slope.  |              |  |      |      |      |      |      |  |
| 16.00        | Ridge, bears E. and W.; desc. N. slope.   |              |  |      |      |      |      |      |  |
| 20.015       | Point for the N 1/16 sec. cor. of secs. 31 and 32.<br><br>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.<br><br><div style="text-align: center;"> <table border="0"> <tr><td colspan="2">N 1/16</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2">1992</td></tr> </table> </div><br>from which<br><br>A fir, 17 ins. diam., bears N. 28° E., 80 lks. dist., mkd. N 1/16 S32 BT.<br><br>A fir, 17 ins. diam., bears N. 55° W., 36 lks. dist., mkd. N 1/16 S31 BT.<br><br>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.  | N 1/16       |  | S 31 | S 32 | 1992 |      |      |  |
| N 1/16       |   |              |  |      |      |      |      |      |  |
| S 31         | S 32  |              |  |      |      |      |      |      |  |
| 1992         |   |              |  |      |      |      |      |      |  |
| 33.00        | Descend NE. slope.  |              |  |      |      |      |      |      |  |
| 40.030       | The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.<br><br><div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T 5 S R 41 E</td></tr> <tr><td>S 30</td><td>S 29</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2">1971</td></tr> </table> </div><br>from which the remains of the original bearing trees<br><br>A root hole, bears N. 12° E., 30 lks. dist.<br><br>A loose piece of pine wood with scribe marks BT, bears S. 68° E., 22 lks. dist.<br><br>A ponderosa pine, 21 ins. diam., bears S. 21° W., 14 lks. dist., no marks. (Record, S. 19° W.)<br><br>A ponderosa pine, 40 ins. diam., bears N. 89½° W., 19 lks. dist., with healed blaze.<br><br>and bearing trees mkd. by Albright<br><br>A lodgepole pine, 14 ins. diam., bears N. 53½° E., 168 lks. dist., mkd. T5S R41E S29 BT on open blaze. (Record, N. 55½° E., 165 lks.) | T 5 S R 41 E |  | S 30 | S 29 | S 31 | S 32 | 1971 |  |
| T 5 S R 41 E |   |              |  |      |      |      |      |      |  |
| S 30         | S 29  |              |  |      |      |      |      |      |  |
| S 31         | S 32  |              |  |      |      |      |      |      |  |
| 1971         |   |              |  |      |      |      |      |      |  |

|                          |                  |
|--------------------------|------------------|
| UNION COUNTY<br>SURVEYOR |                  |
| Date Received            | 3/5/13           |
| Date Filed               | 3/5/13           |
| By                       | <i>RL Ollman</i> |
| File No.                 | 149-2013R        |