


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

60.84 Point set for the center N 1/16 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 30 ins. in the ground to solid rock, with brass cap, from which:



A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S.54°15'W., 0.412 chs. dist., with brass cap mkd. RM CN 1/16 S34 27.2 FT TO COR 1992 and an arrow pointing to the corner. Set a steel fence post alongside the reference monument. A ponderosa pine, 25 ins. diam., bears N.17°W., 61 lks. dist. mkd. CN 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located in the westerly edge of track road, 15 lks. wide, extending N.20°E. and S.20°W.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 2" below ground, from which:

A pine, 14" diam., bears S.14°15'E., 45.74', with a 13" x 3" blaze, scribed "N1/16 S34 BT".

A pine, 25" diam., bears N.17°01'W., 40.50', with a 15"x 3" blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY
SURVEYOR

Date Received 10/18/84

Date Filed 10/23/84

By [Signature]

File No. 123-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature] 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19__

(COUNTY OFFICIAL)

(DEPUTY)

AB

W-15

504

Subdivision of Section 34,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
54.00	Track road, 15 lks. wide, bears N. 20° E. and S. 20° W.
60.840	<p>Point for the center N 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 30 ins. in the ground to solid rock, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 34 \\ C \\ 1992 \end{array}$ </div> <p>from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 54° 15' W., 0.412 chs. dist., with brass cap mkd. RM CN 1/16 S34 27.2 FT TO COR 1992 and an arrow pointing to the corner. Set a steel fence post alongside the reference monument.</p> <p>A ponderosa pine, 25 ins. diam., bears N. 17° W., 61 lks. dist., mkd. CN 1/16 S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the corner post.</p> <p>The corner is located in the westerly edge of a track road, 15 lks. wide, extending N. 20° E. and S. 20° W.</p>
67.50	Spur, slopes E., along rolling E. slope.
81.070	<p>The ¼ sec. cor. of secs. 27 and 34.</p> <hr/> <p>From the ¼ sec. cor. of secs. 34 and 35.</p> <p>S. 89° 44' 00" W., on the E. and W. center line of sec. 34.</p> <p>Over broad spur, sloping S., through logged area.</p>
2.00	Descend gradual SW. slope.
5.00	Descend W. slope.
20.010	<p>Point for the center E 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E\ 1/16 \\ C \quad \frac{\quad}{\quad} \quad C \\ S\ 34 \\ 1992 \end{array}$ </div> <p>from which</p> <p>A ponderosa pine, 22 ins. diam., at the corner of wire fences extending E. and N., bears N. 22° E., 103 lks. dist., mkd. CE 1/16 S34 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>R. G. [Signature]</i>
File No.	150-2013R