

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
19.50	Barbed wire fence, bears E. and W.
22.50	Descend NW. slope, to ravine; thence ascend.
40.175	The ¼ sec. cor. of secs. 34 and 35, monumented with the original slate stone, 19 x 11 x 5 ins., firmly set, projecting 3 ins. above ground, with illegible chisel marks on the E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T 5 S R 41 E</p> <p>S 34 S 35</p> <p>1991</p>
	from which new bearing trees
	A ponderosa pine, 20 ins. diam., bears N. 2½° E., 140 lks. dist., mkd. ¼ S35 BT.
	A ponderosa pine, 19 ins. diam., bears N. 19¼° W., 156 lks. dist., mkd. ¼ S34 BT.
	Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.
	From this point, a decayed pine stump, size indeterminate, no marks visible, bears South, 1.975 chs. dist.
	N. 0° 19' 30" W., beginning new measurement.
	Ascend S. slope, through logged area.
1.40	Barbed wire fence, extends E. and W., leave logged area; enter timber.
14.00	Descend NW. slope.
20.320	Point for the N 1/16 sec. cor. of secs. 34 and 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>N 1/16</p> <p>S 34 S 35</p> <p>1991</p>
	from which
	A fir, 12 ins. diam., bears N. 37° E., 69 lks. dist., mkd. N 1/16 S35 BT.
	A fir, 17 ins. diam., bears N. 24° W., 80 lks. dist., mkd. N 1/16 S34 BT.

UNION COUNTY SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 152-2013R