


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A pine, 15" diam., bears N.02°38'E., 32.55', with a 15" x 4" blaze, scribed "C¼ S31BT".
- A pine, 17" diam., bears S.61°16'E., 23.84', with a 17" x 3½" blaze, scribed "C¼ S31BT".
- A fir, 26" diam., bears S.06°12'W., 54.82', with a 14" x 4" blaze, scribed "C¼ S31BT".
- A fir, 14" diam., bears N.65°42'W., 19.23', with a 15" x 4" blaze, scribed "C¼ S31BT".

UNION COUNTY SURVEYOR

Date Received 10/18/94

Date Filed 10/23/94

By Guyton T. Black

File No. 126-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

AE

X-3