

X-5 T55 R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON Post set 24" in Ground with
5' steel Fence Post Along side

T55 R41E BRASS
 V4 CAF
 S31 S32 MKD
 1971

9

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A W. Fir 18" BRS, N40° E 57 LKS MKD 1/4 S32 BT

A W. Fir 12" BRS N43° W 89 LKS MKD 1/4 S31 BT

ORIG BT - Down Fir 12" BRS 362° E 26 LKS with SCR. MKD 1/4 S BT

10

Work Done By S ALBRIGHT Title CADASTRAL SURVEYOR Date 9/22/77 State Registration No. 81M
 Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

11

REMARKS

Did NOT Accept 16" W.F. To NE. AS ORIG. B.T.

12

Index File No.	T.	R.	M.	Tract or Surv. No.	Cor.

13

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-28-87

By G. LANGLITZ, DEPUTY


File No. 438-87R

X-5

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

41.375 The ¼ sec. cor. of secs. 31 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap, from which:



Original bearing trees:

- A root hole, bears S.62°E., 26 lks. dist. with rotten fir wood alongside, with axe marks.
- A root hole, bears S.15°W., 32 lks. dist.

Bearing trees marked by Albright:

- A fir snag, 22 ins. diam., bears N.40°E., 57 lks. dist. with scribe marks ¼ S32 BT visible on open blaze.
- A fir snag, 18 ins. diam., bears N.43°W., 89 lks. dist. with healed blaze.

New bearing trees:

- A fir, 14 ins. diam., bears S.40°E., 63 lks. dist. mkd. ¼ S32 BT.
- A lodgepole pine, 11 ins. diam., bears N.39½°W., 29 lks. dist. mkd. ¼ S 31 BT.

Description of corner evidence found:

Found a 2½ " B.L.M. brass cap, 6" above ground from which:

- A fir snag, 22" diam., bears N.40°30'E., 37.97', with a 16" blaze scribed "¼S32BT".
- A fir, 11" diam., bears S.40°11'W., 41.51', with a 12" blaze, scribed "¼S32BT".
- A fir snag, 14" diam., bears N.43°53'W., 58.79', with a 15" blaze.
- A l. pine, 12" diam., bears N.39°28'W., 19.23', with a 12" blaze, scribed "¼S31BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

UNION COUNTY SURVEYOR

Date Received 10/18/84

Date Filed 10/23/84

By [Signature]

File No. 128-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature] 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

AG

X-5

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 41 E

$\frac{1}{2}$
S 8 | S 9
1971

from which new bearing trees

A ponderosa pine, 10 ins. diam., bears S. 75° E.,
52½ lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A ponderosa pine, 10 ins. diam., bears N. 41½° W.,
96 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Set 5 ft. steel fence post alongside iron post.

The $\frac{1}{2}$ sec. cor. of secs. 31 and 32, determined at record
bearing and distance from the original bearing trees:

A root hole, bears S. 62° E., 26 lks. dist., with
a down fir alongside, 12 ins. diam., with scribe
marks $\frac{1}{4}$ S BT visible on open blaze.

A root hole, bears S. 15° W., 32 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 41 E

$\frac{1}{2}$
S 31 | S 32
1971

from which new bearing trees

A white fir, 18 ins. diam., bears N. 40° E., 57
lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A white fir, 12 ins. diam., bears N. 43° W., 89
lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Set 5 ft. steel fence post alongside iron post.

The cor. of secs. 29, 30, 31, and 32, determined at
record bearing and distance from the remaining original
bearing trees:

A ponderosa pine, 18 ins. diam., bears S. 19° W.,
14 lks. dist., no marks visible.

A ponderosa pine, 31 ins. diam., bears N. 89½° W.,
19 lks. dist., with scribe mark T visible on
open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 5 S R 41 E

S 30 | S 29
S 31 | S 32
1971

from which new bearing trees

**UNION COUNTY
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 018-2013R

481

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

BAGETT GRIFFITH ASSOC

T 4 S R 41 E

S 32

 $\frac{1}{4}$

S 5

T 5 S

1986

OPLS 644

from which bearing trees mkd. by Griffith

A Douglas fir, 16 ins. diam., bears S. 30° W., 58 lks.
dist., with scribe marks $\frac{1}{4}$ S5 BT on open double blaze.

A ponderosa pine, 18 ins. diam., bears N. 21° W., 58 lks.
dist., with scribe marks $\frac{1}{4}$ S32 BT on open double blaze.

From the standard cor. of secs. 31 and 32 on the S. bdy. of the
Tp.

N. 1° 07' 00" E., bet. secs. 31 and 32.

Descend N. slope through logged area.

32.00

Broad spur, sloping E.; desc. NE slope

41.375

The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with an iron post,
2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with
brass cap mkd.

T 5 S R 41 E

S 31 $\frac{1}{4}$ S 32
1971

from which the remains of original bearing trees

A root hole, bears S. 62° E., 26 lks. dist., with
rotten fir wood alongside, with axe marks.

A root hole, bears S. 15° W., 32 lks. dist.

and the remains of bearing trees mkd. by Albright

A fir snag, 22 ins. diam., bears N. 40° E., 57 lks.
dist., with scribe marks $\frac{1}{4}$ S32 BT visible on open blaze.

A fir snag, 18 ins. diam., bears N. 43° W., 89 lks. dist.,
with healed blaze.

and new bearing trees

A fir, 14 ins. diam., bears S. 40° E., 63 lks. dist.,
mkd. $\frac{1}{4}$ S32 BT.

A lodgepole pine, 11 ins. diam., bears N. 39 $\frac{1}{2}$ ° W.,
29 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

File No.

154-2013R