


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

History of original corner establishment:



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A pine, 11" diam., bears N.49°42'E., 31.45', scribed "C¼ S32 BT".
- A pine, 11" diam., bears S.47°39'E., 19.62', scribed "C¼ S32 BT".
- A fir, 8" diam., bears S.71°24'W., 25.15', scribed "C¼ S32 BT".
- A fir, 7" diam., bears N.26°09'W., 14.71', scribed "C¼ S32BT".

UNION COUNTY  
SURVEYOR

---

Date Received 10/19/84

Date Filed 10/23/84

By Guy T. Black

File No. 129-1990R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Ronald E. Stoll 10/94*

OREGON  
JULY 15, 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

AH

X-7