


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

40.29 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate distances; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap, from which:



A lodgepole pine, 9 ins. diam., bears S.21 3/4°E., 78 lks. dist. mkd. 1/4 S33 BT.

A lodgepole pine, 11 ins. diam., bears S.77°W., 13 lks. dist. mkd. 1/4 S32 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

**Description of corner evidence found:**

Found a 2 1/2" B.L.M. brass cap, 5" above ground, with a 2' mound of stone to cap, from which:

A pine, 10" diam., bears S.21°16'E., 51.20', with a 14" x 3" blaze, scribed "1/4 S33 BT".

A pine, 12" diam., bears S.77°54'W., 8.82', with a 18" x 3" blaze, scribed "1/4 S32 BT".

**Description of monument and accessories I established to perpetuate the original location of this corner:**

A tamarack, 12" diam., bears S.48°23'E., 11.40', with a 15" x 5" blaze, scribed "1/4 S33 BT".

A tamarack, 14" diam., bears N.19°38'W., 28.25', with a 15" x 5" blaze, scribed "1/4 S32 BT".

<b>UNION COUNTY SURVEYOR</b>	
Date Received	<u>10/10/84</u>
Date Filed	<u>10/23/84</u>
By	<u>[Signature]</u>
File No.	<u>130-1994R</u>

REGISTERED <b>PROFESSIONAL LAND SURVEYOR</b>
<u>[Signature]</u> 10/94
OREGON JULY 15 1983 RONALD E. STOLL 2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_ day of \_\_\_\_\_, 19\_\_

\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
40.290	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 32   S 33 1991</p> <p>from which</p> <p style="padding-left: 40px;">A lodgepole pine, 9 ins. diam., bears S. 21¼° E., 78 lks. dist., mkd. ¼ S33 BT.</p> <p style="padding-left: 40px;">A lodgepole pine, 11 ins. diam., bears S. 77° W., 13 lks. dist., mkd. ¼ S32 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p> <p>Continue along W. slope through logged area.</p>
43.10	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.
80.10	Graveled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
80.580	<p>Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; the true corner point cannot be determined from the remains of the original evidence, a detached blaze from one of the original bearing trees with the scribe marks BT legible.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground with top flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 29   S 28 S 32   S 33 1991</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A lodgepole pine, 12 ins. diam., bears N. 45½° E., 136 lks. dist., mkd. T5S R41E S28 BT.</p> <p style="padding-left: 40px;">A lodgepole pine, 15 ins. diam., bears S. 58¼° E., 298 lks. dist., mkd. T5S R41E S33 BT.</p> <p style="padding-left: 40px;">A lodgepole pine, 6 ins. diam., bears S. 49¼° W., 367 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 50° W., 431 lks. dist., mkd. T5S R41E S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the remains of the original bearing tree alongside and set two 6 ft. steel fence posts alongside the stainless steel post.</p>

UNION COUNTY  
SURVEYOR

---

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 155-2013R