


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

History of original corner establishment:



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A fir, 9" diam., bears N.32°16'E., 41.80', scribed "C¼ S33 BT".
- A fir, 11" diam., bears S.47°50'E., 37.20', scribed "C¼ S33 BT".
- A tamarack, 13" diam., bears S.53°26'W., 54.41', scribed "C¼ S33 BT".
- A tamarack, 13" diam., bears N.42°04'W., 15.55', scribed "C¼ S33 BT".

UNION COUNTY  
SURVEYOR

---

Date Received 10/10/94

Date Filed 10/23/94

By Guy T. Black

File No. 131-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

Ronald E. Stoll 10/94

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

AJ

X-11