

Subdivision of Section 34,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A larch, 10 ins. diam., bears N. 79° W., 112 lks. dist., mkd. CE 1/16 S34 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Descend SW. slope.</p>
27.00	<p>Oregon State Highway No. 203, paved, 40 lks. wide, bears N. 20° E. and S. 20° W.</p>
30.60	<p>Dry stream, 4 lks. wide, course S.; asc. E. slope.</p>
40.020	<p>The center ¼ sec. cor. of sec. 34.</p>
59.15	<p>Flat spur, bears N. 20° W. and S. 20° E.</p>
59.440	<p>Point for the center W 1/16 sec. cor. of sec. 34.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;"> W 1/16 C ——— C S 34 1992 </p>
	<p>from which</p>
	<p>A ponderosa pine, 12 ins. diam., bears S. 24° W., 33 lks. dist., mkd. CW 1/16 S34 BT.</p>
	<p>A ponderosa pine, 17 ins. diam., bears N. 44½° W., 56 lks. dist., mkd. X at breast height and BT at the base.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Descend SW. slope to creek; thence ascend.</p>
78.860	<p>The ¼ sec. cor. of secs. 33 and 34.</p>
	<p>From the center E 1/16 sec. cor. of sec. 34.</p>
	<p>N. 0° 02' 00" E., on the N. and S. center line of the NE¼ of sec. 34.</p>
	<p>Ascend over SW. slope, through logged area.</p>
1.50	<p>Along broken W. slope.</p>
20.280	<p>Point for the NE 1/16 sec. cor. of sec. 34 at intersection with the E. and W. center line of the NE¼.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> NE 1/16 S 34 1992 </p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>J.L. Galt</i>
File No.	157-2013R