


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

40.61 Point for the center ¼ sec. cor. of secs. 34 at intersections with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, and in a collar of stone, with brass cap, from which:



A ponderosa pine, 20 ins. diam., bears S.85½°W., 90 lks. dist. mkd. x at breast height and BT at the base.

A ponderosa pine, 20 ins. diam., bears N.27°W., 156 lks. dist. mkd. C¼ S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.

The corner is located at the easterly edge of a seldom used track road, 15 lks. wide, extending N.35°W and S.35°E.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, flush with ground, with a 2' mound of stone to cap, from which:

A pine, 20" diam., bears N.27°07'W., 102.67', with a 16" x 4" blaze, scribed "C¼ S34 BT".

A pine, 19" diam., bears S.85°30'E., 58.95', with a 5" x 2" blaze, scribed "X" at breast height".

Description of monument and accessories I established to perpetuate the original location of this corner:

A pine, 25" diam., bears N.24°08'E., 43.89', scribed "C¼ S34 BT".

A fir, 33" diam., bears S.70°46'E., 51.39', scribed "BT".

UNION COUNTY SURVEYOR
Date Received 10/18/94
Date Filed 10/23/94
By Gregory T. Black
File No 133-1994R

REGISTERED PROFESSIONAL LAND SURVEYOR
Ronald E. Stoll 10/94
OREGON JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Subdivision of Section 10,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
39.675	<p>The center N 1/16 sec. cor. of sec. 10.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 31' 30" W., on the N. and S. center line of the SE¼ of sec. 10.</p> <p>Ascend gradually over SW. slope changing to W. slope, through medium timber and light undergrowth.</p>
39.775	<p>The center E 1/16 sec. cor. of sec. 10.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 5 S., R. 41 E., Willamette Meridian, Oregon</p> <hr/> <p>From the standard ¼ sec. cor. of sec. 34 on the S. bdy. of the Tp.</p> <p>N. 0° 22' 30" E., on the N. and S. center line of sec. 34.</p> <p>Descend NE. slope, through medium timber and undergrowth.</p> <p>15.50 Bottom of descent; along gradual E. slope.</p> <p>27.480 From this point, a point established by Norman J. Paullus, Jr., Registered Land Surveyor No. 1952, in 1991, and recorded under file No. 047-1991 of Union County Records, bears West, 0.308 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set with top flush with the ground, with plastic cap mkd. PCA LS 1952.</p> <p>27.50 Barbed wire fence, extends E. and W.</p>
40.610	<p>Point for the center ¼ sec. cor. of sec. 34 at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E C¼ S 34 1992</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 85½° W., 90 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 27° W., 156 lks. dist., mkd. C¼ S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a steel fence post alongside the stainless steel post.</p> <p>The corner is located at the easterly edge of a seldom used track road, 15 lks. wide, extending N. 35° W. and S. 35° E.</p> <p>Ascend SE. slope.</p>

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By



File No.

158-201312