

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**History of original corner establishment:**

20.01 Point for the center E1/16 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap, from which:

A ponderosa pine, 22 ins. diam., at the corner of wire fences extending E. and N., bears N.22°E., 103 lks. dist. mkd. CE 1/16 S34 BT.

A larch, 10 ins. diam., bears N.79°W., 112 lks. dist. mkd. CE 1/16 S34 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.



**Description of corner evidence found:**

Found a 2½" B.L.M. brass cap, 3" above ground, with a 2" collar, from which:

A pine, 20" diam., bears N.21°35'E., 107.86', with a 15" x 3" blaze, scribed "CE1/16 S34 BT".

A fir, 10" diam., bears N.79°19'W., 74.45', with a 15" x 2" blaze, scribed "CE1/16 S34 BT".

**Description of monument and accessories I established to perpetuate the original location of this corner:**

UNION COUNTY SURVEYOR

Date Received 10/18/94

Date Filed 10/23/94

By Guy ToBlack

File No. 134-1094R

REGISTERED PROFESSIONAL LAND SURVEYOR

RW & Stoll 10/94

OREGON  
JULY 15 1983  
RONALD E STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

AM

*A-16*

504

Subdivision of Section 34,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
54.00	Track road, 15 lks. wide, bears N. 20° E. and S. 20° W.
60.840	Point for the center N 1/16 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 30 ins. in the ground to solid rock, with brass cap mkd.
	$\begin{array}{c} C \\ N\ 1/16 \quad   \quad S\ 34 \\ C \\ 1992 \end{array}$
	from which
	A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 54° 15' W., 0.412 chs. dist., with brass cap mkd. RM CN 1/16 S34 27.2 FT TO COR 1992 and an arrow pointing to the corner. Set a steel fence post alongside the reference monument.
	A ponderosa pine, 25 ins. diam., bears N. 17° W., 61 lks. dist., mkd. CN 1/16 S34 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the corner post.
	The corner is located in the westerly edge of a track road, 15 lks. wide, extending N. 20° E. and S. 20° W.
67.50	Spur, slopes E., along rolling E. slope.
81.070	The ¼ sec. cor. of secs. 27 and 34.
	From the ¼ sec. cor. of secs. 34 and 35. S. 89° 44' 00" W., on the E. and W. center line of sec. 34. Over broad spur, sloping S., through logged area.
2.00	Descend gradual SW. slope.
5.00	Descend W. slope.
20.010	Point for the center E 1/16 sec. cor. of sec. 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	$\begin{array}{c} E\ 1/16 \\ C \quad \frac{\quad}{\quad} \quad C \\ S\ 34 \\ 1992 \end{array}$
	from which
	A ponderosa pine, 22 ins. diam., at the corner of wire fences extending E. and N., bears N. 22° E., 103 lks. dist., mkd. CE 1/16 S34 BT.

UNION COUNTY  
SURVEYOR

---

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 159-2013R

Subdivision of Section 34,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A larch, 10 ins. diam., bears N. 79° W., 112 lks. dist., mkd. CE 1/16 S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	<p>Descend SW. slope.</p>
27.00	<p>Oregon State Highway No. 203, paved, 40 lks. wide, bears N. 20° E. and S. 20° W.</p>
30.60	<p>Dry stream, 4 lks. wide, course S.; asc. E. slope.</p>
40.020	<p>The center ¼ sec. cor. of sec. 34.</p>
59.15	<p>Flat spur, bears N. 20° W. and S. 20° E.</p>
59.440	<p>Point for the center W 1/16 sec. cor. of sec. 34.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>W 1/16 C ——— C S 34 1992</p> </div> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 24° W., 33 lks. dist., mkd. CW 1/16 S34 BT.</p> <p>A ponderosa pine, 17 ins. diam., bears N. 44½° W., 56 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend SW. slope to creek; thence ascend.</p>
78.860	<p>The ¼ sec. cor. of secs. 33 and 34.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 34.</p> <p>N. 0° 02' 00" E., on the N. and S. center line of the NE¼ of sec. 34.</p> <p>Ascend over SW. slope, through logged area.</p>
1.50	<p>Along broken W. slope.</p>
20.280	<p>Point for the NE 1/16 sec. cor. of sec. 34 at intersection with the E. and W. center line of the NE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S 34 1992</p> </div>

UNION COUNTY  
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By NA G Allen

File No. 159-2013R