

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	(Restoring the survey by Henry M. Thatcher, in 1879, and the remonumentation by Steven D. Albright, in 1971)
	From the standard cor. of secs. 35 and 36 on the S. bdy. of the Tp.
	N. 0° 38' 00" E., bet. secs. 35 and 36.
	Ascend SW. slope.
4.00	Spur, slopes N. 60° W.
24.30	Graveled road, 25 lks. wide, bears N. 70° E. and S. 70° W., on ridge bearing the same.
35.50	Ravine, drains W. asc. S. slope.
40.560	Point for the ¼ sec. cor. of secs. 35 and 36 at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 5 S R 41 E S 35 S 36 1991 </div> from which A fir, 26 ins. diam., bears N. 85½° E., 71 lks. dist., mkd. ¼ S36 BT. A larch, 15 ins. diam., bears N. 80¼° W., 72 lks. dist., mkd. ¼ S35 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Ascend SW. slope.
74.00	Descend NE. slope.
81.120	The cor. of secs. 25, 26, 35, and 36, perpetuated and recorded by James G. Voelz, Registered Land Surveyor No. 381, in 1969, recorded under file No. 725-84R, monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center;"> COR T 5 S R 41 E S 26 S 25 S 35 S 36 ORE LIC 381 1969 </div> from which the remains of the original bearing trees

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By N. L. G. Albright

File No. 161-2013R