

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

BAGETT GRIFFITH AND ASSOC

T 4 S R 41 E

S 33 | S 34

S 4 | S 3

T 5 S

1986

OPLS 644

from which bearing trees mkd. by Griffith

A ponderosa pine, 14 ins. diam., bears N. 85° E.,  
72 lks. dist., with fragmentary scribe marks on  
partially healed double blaze.

A ponderosa pine, 21 ins. diam., bears S. 4° E.,  
55 lks. dist., with fragmentary scribe marks on  
partially healed double blaze.

A fir, 10 ins. diam., bears S. 83° W., 47 lks. dist.,  
mkd. X BT on open double blaze.

A ponderosa pine, 20 ins. diam., bears N. 59° W.,  
55 lks. dist., with fragmentary scribe marks on  
partially healed double blaze.

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

M. L. Gilman

File No.

163-203R

From the standard cor. of secs. 32 and 33 on the S. bdy. of the  
Tp.

N. 0° 35' 30" E., bet. secs. 32 and 33.

Descend gradual N. slope through medium timber and light  
undergrowth.

20.145

Point for the S 1/16 sec. cor. of secs. 32 and 33.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

S 1/16  
S 32 | S 33  
1991

from which

A lodgepole pine, 14 ins. diam., bears N. 48¼° E.,  
159 lks. dist., mkd. S 1/16 S33 BT.

A lodgepole pine, 17 ins. diam., bears N. 41¾° W.,  
50 lks. dist., mkd. S 1/16 S32 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6  
ft. steel fence post alongside the stainless steel post.

Descend N. slope through logged area.

24.50

Ravine, drains N. 30° W.; desc. NW. slope through logged area.

38.25

Dirt road, 15 lks. wide, bears N. 30° W. and S. 30° E.