


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

History of original corner establishment:



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set monument 24" in ground with mound of stone to cap, from which:

- A fir, 9" diam., bears N.59°26'E., 58.38', with a 18" x 4" blaze, scribed "CS1/16 S33 BT".
- A  $\frac{1}{2}$ " iron pipe set, 4" above ground, bears S.81°33'W., 32.39', with a plastic cap, marked "LS2058".
- A  $\frac{1}{2}$ " iron pipe, 2' above ground, bears N.10°30'W., 10.38', with a plastic cap, marked "LS2058".

**UNION COUNTY SURVEYOR**

---

Date Received 10/10/94

Date Filed 10/23/94

By [Signature]

File No. 136-1994R

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

[Signature] 10/94

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

AO

Y-11