

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**History of original corner establishment:**

20.37 Point for the S. 1/16 sec. cor. of secs. 33 and 34. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

A fir, 17 ins. diam., bears N.15°E., 49 lks. dist. mkd. S 1/16 S34 BT.

A larch, 11 ins. diam., bears N.59°W., 47 lks. dist. mkd. S 1/16 S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.



**Description of corner evidence found:**

Found a 2½" B.L.M. brass cap, 3" above ground, from which:

A larch, 11" diam., bears N.58°22'W., 31.23', with a 16" x 4" blaze, scribed "S1/16 S33 BT".

A fir, 15" diam., bears N.15°40'E., 31.78', with a 16" x 5" blaze, scribed "S1/16 S33 BT".

**Description of monument and accessories I established to perpetuate the original location of this corner:**

UNION COUNTY SURVEYOR

Date Received 10/18/84

Date Filed 10/23/84

By [Signature]

File No 137-1994R

REGISTERED PROFESSIONAL LAND SURVEYOR

[Signature] 10/94

OREGON  
JULY 15 1983  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
 for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_  
 \_\_\_\_\_ by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

AP

Y-13

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

20.370

Point for the S 1/16 sec. cor. of secs. 33 and 34.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16  
S 33 | S 34  
1991

from which

A fir, 17 ins. diam., bears N. 15° E., 49 lks. dist., mkd. S 1/16 S34 BT.

A larch, 11 ins. diam., bears N. 59° W., 47 lks. dist., mkd. S 1/16 S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

39.50

Spring branch, 2 lks. wide, course E.

40.740

The ¼ sec. cor. of secs. 33 and 34, monumented with the original slate stone, 19 x 15 x 5 ins., loosely set 1 in. in the ground, mkd. ¼ on the W. face, from which the remains of the original bearing trees:

A root hole, bears S. 85° E., 22 lks. dist.

A root hole, bears N. 50° W., 10 lks. dist., with fir log, 38 ins. diam., alongside, with open blaze, no marks remain on burned rotting face deep within.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E  
S 33 ¼ | S 34  
1991

from which new bearing trees

A ponderosa pine, 18 ins. diam., bears S. 21° E., 40 lks. dist., mkd. ¼ S34 BT.

A larch, 11 ins. diam., bears S. 82¼° W., 53 lks. dist., mkd. ¼ S33 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.

The corner is located on a spur, sloping S. 65° E.

N. 0° 37' 00" W., beginning new measurement.

3.00

Ascend S. slope.

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

*[Signature]*

File No.

1164-201312