


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original survey by N.O. Walden, under Contract No. 198, dated July 15, 1873:

Extension of 1st Standard Parallel South; set slate stone, 20x10x3, 8 in. in ground for corner to T5 & 6S of Range 40, 41 east. Built mound of rocks. August 13, 1873.

Subsequent surveys established closing corners on the 1st, Standard Parallel for Townships to the South.



Description of corner evidence found:

Found the original basalt corner stone 20"x10"x3" out of position and lying loose on the ground, approx. 5' from the remains of the original stone mound, with chiseled markings as follows:

- "R40" and 6 notches on a face,
- "T5S" on an edge,
- "R41" and 6 notches on a face. The remaining edge has weathered, no marks found.

Description of monument and accessories established to perpetuate the original location of this corner:

At the original corner point determined to be in the center of the original stone mound, we set a 2"x30" aluminum pipe, 22" in the ground and in a small mound of stone, with aluminum cap, marked:

We bury the original corner stone along the east side of the the aluminum pipe, from which we mark the following bearing trees:

A 14" Ponderosa Pine, scribed "SC T5SR40E S36 BT" on a double blaze, bears N64°W 103.3 feet.

And a 14" Ponderosa Pine, scribed "SC T5S R41E S31 BT" on a double blaze, bears N63°E 95.1 feet.

Attached brass washer, marked "LS 1099" to lower blaze of new bearing trees.

Placed steel fence post with "Attention" sign attached approx. 7 ft. north of corner.


Staff compass (21° East Declination) steel tape.

UNION COUNTY SURVEYOR
T5S
R40E SC R41E
S36 | S31
S6
T6S R41E
PLS 1099
1984

August 6, 1984

Witnesses:

Gary Langlitz, Deputy County Surveyor
Dave Dahlstrom, U.S.F.S.
Greg Quibell



Corner is located on a moderate SE slope in scattered Pine and Sagebrush.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	8-24-84
Date Filed	8-24-84
By	G. LANGLITZ, DEPUTY
File No.	932-84 R

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
16.00	Descend SW. slope.
38.50	A spring of flowing water, drains S.
39.460	<p>The standard cor. of Tps. 5 S., Rs. 40 and 41 E., perpetuated from original evidence no longer visible and recorded by Gary L. Langlitz, Union County Deputy Surveyor, in 1984, recorded under file No. 932-84R, monumented with an aluminum pipe, 2 ins. diam., firmly set, projecting 10 ins. above a mound of stone, 3 ft. diam., with aluminum cap mkd.</p> <p style="text-align: center;">UNION COUNTY SURVEYOR T 5 S R 40 E R 41 E SC S 36 S 31 S 6 T 6 S R 41 E PLS 1099 1984</p> <p>from which bearing trees mkd. by Langlitz</p> <p>A ponderosa pine, 16 ins. diam., bears N. 61° E., 143 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>A ponderosa pine, 16 ins. diam., bears N. 65½° W., 156 lks. dist., with scribe marks SC T5S R40 S36 visible on upper blaze and BT visible on lower blaze.</p> <p>A steel fence post is set alongside the aluminum post.</p> <p>From this point, United States Geological Survey triangulation station "REEVES," bears N. 19° 06' 30" E., 39.595 chs. dist., monumented with a standard brass cap, firmly set in bedrock, with top mkd. US GEOLOGICAL SURVEY REEVES 1964 and a triangle at the center.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>JL G/M</i>
File No.	165-2013R

Dependent Resurvey of a Portion of the East Boundary, T. 5 S., R. 41 E., Willamette Meridian, Oregon	
(Restoring the survey by Henry M. Thatcher, in 1879, and the resurvey by James P. Curran, in 1898)	
From the standard cor. of Tps. 5 S., Rs. 41 and 42 E. N. 0° 02' 00" E., on the E. bdy. of sec. 36. Descend NE. slope.	
1.05	Graveled road, 30 lks. wide, bears N. 50° W. and S. 50° E.
40.325	The ¼ sec. cor. of sec. 36 only, determined in the root hole of the original corner tree, from which the remaining original bearing tree: