

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

40.03 The standard ¼ sec. cor. of sec. 32, monumented with the original slate stone, 16 x 15 x 5 ins., loosely set 3 ins. in the ground, mkd. ¼ on the N. face, from which:

A root hole, bears N.40°E., 15 lks. dist., with rotten remains of a large pine log alongside, no marks.

Set a stainless steel post, 28 ins. long, 2½ ins diam., 22 ins. in the ground, and in a collar of stone, with brass cap, from which:

A ponderosa pine, 19 ins. diam., bears N.33½°E., 21 lks. dist. mkd. ¼ S32 SC BT.
 A ponderosa pine, 16 ins. diam., bears N.02°W., 25 lks. dist. mkd. x at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.


Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 6" above ground, with a 1.5' mound of stone to cap, from which:

A pine, 20" diam., bears N.33°10'E., 14.14', with an open blaze (not legible).
 A pine, 15" diam., bears N.02°19'W., 16.76', with an open blaze, scribed "x" at breast height.

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 11" diam., bears S.26°05'E., 33.09', scribed "¼ S32 SC BT".
 A pine, 6" diam., bears S.66°41'W., 11.35', scribed "¼ S32 SC BT".



UNION COUNTY SURVEYOR

Date Received 10/10/94

Date Filed 10/23/94

By Henry T. Clark

File No. 139-1994R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

RW & Stoll 10/94

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____

_____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

AR


2-7

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

40.03 The standard 1/4 sec. cor. of sec. 32, monumented with the original slate stone, 16 x 15 x 5 ins., loosely set 3 ins. in the ground, mkd. 1/4 on the N. face, from which:



A root hole, bears N.40°E., 15 lks. dist., with rotten remains of a large pine log alongside, no marks.

Set a stainless steel post, 28 ins. long, 2 1/2 ins diam., 22 ins. in the ground, and in a collar of stone, with brass cap, from which:

A ponderosa pine, 19 ins. diam., bears N.33 1/2°E., 21 lks. dist. mkd. 1/4 S32 SC BT.

A ponderosa pine, 16 ins. diam., bears N.02°W., 25 lks. dist. mkd. x at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 6" above ground, with a 1.5' mound of stone to cap, from which:

A pine, 20" diam., bears N.33°10'E., 14.14', with an open blaze (not legible).

A pine, 15" diam., bears N.02°19'W., 16.76', with an open blaze, scribed "x" at breast height.

REFERENCE: RECORD OF SURVEY, FRAIZER CADASTRAL SURVEY
REFERENCE: CORNER MONUMENT RECORD NO.

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 11" diam., bears S.26°05'E., 33.09', scribed "1/4 S32 SC BT".

A pine, 6" diam., bears S.66°41'W., 11.35', scribed "1/4 S32 SC BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY

WITNESS TO MONUMENT: DAVID SUTHERLAND

BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.

BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR
Date Received 10/28/98
Date Filed 10/31/98
by R. ROBINSON, DEPUTY
File No. 103-199BR

REGISTERED PROFESSIONAL LAND SURVEYOR
Ronald E. Stoll 9/98
OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19__

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
12.380	<p>From this point, the original closing cor. of secs. 4 and 5, T. 6 S., R. 41 E., bears South, 0.109 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A larch snag, 17 ins. diam., bears S. 9° W., 28 lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 5 S R 41 E</p> <p style="margin-left: 40px;">S 32</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 5 S 4</p> <p>T 6 S R 41 E</p> <p style="margin-left: 40px;">CC</p> <p style="margin-left: 40px;">1991</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A larch, 14 ins. diam., bears S. 41° E., 133 lks. dist., mkd. T6S R41E S4 CC BT.</p> <p style="padding-left: 40px;">A lodgepole pine, 12 ins. diam., bears S. 67° W., 74 lks. dist., mkd. T6S R41E S5 CC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p>
15.00	Top of ascent, over nearly level land.
34.00	Ascend E. slope.
38.85	Rocky spur, slopes SE.
40.030	<p>The standard ¼ sec. cor. of sec. 32, monumented with the original slate stone, 16 x 15 x 5 ins., loosely set 3 ins. in the ground, mkd. ¼ on the N. face, from which the remains of the original bearing tree:</p> <p style="padding-left: 40px;">A root hole, bears N. 40° E., 15 lks. dist., with rotten remains of a large pine log alongside, no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T 5 S R 41 E</p> <p style="margin-left: 40px;">¼ S 32</p> <hr style="width: 20%; margin: 0 auto;"/> <p style="margin-left: 40px;">1991</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. 33½° E., 21 lks. dist., mkd. ¼ S32 SC BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. G. [Signature]</i>
File No.	168-2013R

Dependent Resurvey of the South Boundary
(First Standard Parallel South),
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS									
	<p>A ponderosa pine, 16 ins. diam., bears N. 2° W., 25 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.</p>								
39.770	<p>S. 89° 55' 30" W., beginning new measurement.</p> <p>Descend steep SW. slope, over numerous slate rock outcrops and cliffs.</p> <p>The standard cor. of secs. 31 and 32, determined at record distance from the remains of the original bearing trees:</p> <p>A sawed, rotting fir stump, 15 ins. diam., bears N. 56° E., 184 lks. dist., no marks. (Record, N. 53° E.)</p> <p>A hollow, burned pine stump, 30 ins. diam., bears West, 40 lks. dist., with burned pine log alongside, with axe marks on weathered blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr><td colspan="2">SC</td></tr> <tr><td>T 5 S</td><td>R 41 E</td></tr> <tr><td>S 31</td><td>S 32</td></tr> <tr><td colspan="2">1991</td></tr> </table> </div>	SC		T 5 S	R 41 E	S 31	S 32	1991	
SC									
T 5 S	R 41 E								
S 31	S 32								
1991									
<div style="border: 1px solid black; padding: 5px;"> <p>UNION COUNTY SURVEYOR</p> <hr/> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>[Signature]</u></p> <p>File No. <u>168-2013R</u></p> </div>	<p>from which new bearing trees</p> <p>The S½ of a twin ponderosa pine, 20 ins. diam., bears N. 7½° E., 98 lks. dist., mkd. T5S R41E S32 SC BT.</p> <p>A ponderosa pine, 18 ins. diam., bears N. 76¼° W., 72 lks. dist., mkd. T5S R41E S31 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>								
12.485	<p>S. 89° 52' 00" W., on the S. bdy. of sec. 31.</p> <p>Along N. slope, through logged area.</p> <p>From this point, the original closing cor. of secs. 5 and 6, T. 6 S., R. 41 E., bears South, 0.068 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A root hole, bears N. 33° E., 43 lks. dist., with a piece of fir log alongside with scribe marks T5S E legible.</p> <p>A sawed fir stump, 28 ins. diam., bears S. 70° E., 45 lks. dist., with scribe marks BT on open blaze.</p>								