


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484



The standard cor. of secs. 32 and 33, monumented with the remains of the bottom of the original corner tree in place, size indeterminate, with loose pieces of tree alongside, with circular scribe mark on weathered blaze, from which the remains of an original bearing tree:

A root hole with burned wood within, bears N.50°E., 33 lks. dist.
A rotten remains of a pine stump, upright in place, size indeterminate, bears N.30°W., 78 lks. dist. no marks.

Set a stainless steel post 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap, from which:

A lodgepole pine, 12 ins. diam., bears N.18½°E., 64 lks. dist. mkd. T5S R41E S33 SC BT.
A larch, 15 ins. diam., bears N.53 3/4°W., 16 lks. dist. mkd. T5S R41E S32 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base, the remains of the corner tree alongside and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 8" above the ground with small stone mound, with 'T' post 2'± South of corner, from which:

A fir, 18" diam., bears N.53°26'W., 10.36', with a 25" x 4" blaze, scribed "T5S R41E S32 SC BT".
A fir, 14" diam., bears N.18°18'E., 42.53', with a 20" x 4" blaze, scribed "T5S R41E S33 SC BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 15" diam., bears S.20°27'E., 36.87', with a 8" x 4" blaze, scribed "BT".
A pine, 20" diam., bears S.73°45'W., 42.97', with a 8" x 5" blaze, scribed "X BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

SURVEYOR <hr/> Date Received <u>10/28/98</u> Date Filed <u>10/31/98</u> By <u>R. Robinson Deputy</u> File No. <u>107.1998R</u>	REGISTERED PROFESSIONAL LAND SURVEYOR <hr/> <hr/> OREGON JULY 15, 1933 RONALD E. STOLL 2058
--	---

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>M. Gilmer</u></p> <p>File No. <u>169-2013R</u></p>	<p style="text-align: center;">SC W 1/16 S 33 1991</p> <p>from which</p> <p>A lodgepole pine, 7 ins. diam., bears N. 10½° E., 47 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A lodgepole pine, 10 ins. diam., bears N. 22° W., 54 lks. dist., mkd. W 1/16 S33 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend gradual NW. slope.</p> <p>69.50 Gravel road, 25 lks. wide, bears N. 30° E. and S. 30° W.</p>
<p>79.720</p>	<p>The standard cor. of secs. 32 and 33, monumented with the remains of the bottom of the original corner tree in place, size indeterminate, with loose piece of tree alongside, with circular scribe mark on weathered blaze, from which the remains of the original bearing trees:</p> <p>A root hole with burned wood within, bears N. 50° E., 33 lks. dist.</p> <p>The rotted remains of a pine stump, upright in place, size indeterminate, bears N. 30° W., 78 lks. dist., no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T 5 S R 41 E S 32 S 33 1991</p> <p>from which new bearing trees</p> <p>A lodgepole pine, 12 ins. diam., bears N. 18½° E., 64 lks. dist., mkd. T5S R41E S33 SC BT.</p> <p>A larch, 15 ins. diam., bears N. 53¾° W., 16 lks. dist., mkd. T5S R41E S32 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the remains of the corner tree alongside and set a 6 ft. steel fence post alongside the stainless steel post.</p>
<p>4.25</p>	<p>S. 89° 29' 00" W., on the S. bdy. of sec. 32.</p> <p>Track road, 15 lks. wide, bears N. 40° E. and S. 40° W.; asc. gradual E. slope.</p>