

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

59.790 Point for the standard W 1/16 sec. cor, of sec. 33.

Set a stainless steel post 28 ins long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

A lodgepole pine, 7 ins. diam., bears N.10 1/2°E., 47 lks. dist. mkd. X at breast height and BT at base.

A lodgepole pine, 10 ins. diam., bears N.22°W., 54 lks. dist. mkd. W1/16 S33 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 4" above ground, with no mound of stone to cap, from which:


A lodgepole pine, 7 ins. diam., bears N.10°30'E., 30.9' dist. mkd. BT

A lodgepole pine(dead), 10 ins. diam., bears N.19°30'W., 40.4' dist. mkd. W1/16 S33 SC BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

A tamarack, 18 ins. diam., bears N.57°00'E., 29.8' dist. mkd. SCW1/16 S33 BT.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: ERIC GREEN
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY
SURVEYOR

Date Received 10/28/98
Date Filed 10/31/98
By R. ROBINSON, DEPUTY
File No. 106-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald E. Stoll 9/98
OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	SC E 1/16 <u>S 33</u> 1991
	from which A larch, 18 ins. diam., bears N. 81° E., 9 lks. dist., mkd. E 1/16 S33 SC BT. A lodgepole pine, 13 ins. diam., bears N. 87° W., 44 lks. dist., mkd. E 1/16 S33 SC BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
35.50	Narrow, rocky ridge, bears N. 10° W. and S. 10° E.; desc. W. slope.
39.860	Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	SC T 5 S R 41 E <u>¼ S 33</u> 1991
	from which A fir, 15 ins. diam., bears N. 23° E., 34 lks. dist., mkd. ¼ S33 SC BT. A lodgepole pine, 7 ins. diam., bears N. 26° W., 48 lks. dist., mkd. X at breast height and BT at the base. Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post. From this point, United States Geological Survey triangulation station "FRAZIER," as determined from a tie to the original reference monument No. 1, bears S. 13° 29' 00" W., 17,805 chs. dist. The triangulation station has been destroyed. Reference monument No. 1, located S. 48° 13' 20" W., 21.74 ft. from the true position, is monumented with a standard brass cap firmly set in bedrock with top marked US GEOLOGICAL SURVEY REFERENCE MARK NO 1 1964 and an arrow pointing to the true station. Descend gradual W. slope.
59.790	Point for the standard W 1/16 sec. cor. of sec. 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	M.L. G. [Signature]
File No.	170-2013R

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

<p>CHAINS</p>	<p style="text-align: center;">SC W 1/16 <u>S 33</u> 1991</p> <p>from which</p> <p>A lodgepole pine, 7 ins. diam., bears N. 10½° E., 47 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A lodgepole pine, 10 ins. diam., bears N. 22° W., 54 lks. dist., mkd. W 1/16 S33 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
<p>69.50 79.720</p>	<p>Descend gradual NW. slope.</p> <p>Gravel road, 25 lks. wide, bears N. 30° E. and S. 30° W.</p> <p>The standard cor. of secs. 32 and 33, monumented with the remains of the bottom of the original corner tree in place, size indeterminate, with loose piece of tree alongside, with circular scribe mark on weathered blaze, from which the remains of the original bearing trees:</p> <p>A root hole with burned wood within, bears N. 50° E., 33 lks. dist.</p> <p>The rotted remains of a pine stump, upright in place, size indeterminate, bears N. 30° W., 78 lks. dist., no marks.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC T 5 S R 41 E <u>S 32 S 33</u> 1991</p>
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p><i>W. L. G. [Signature]</i></p> <p>No. <u>170-2013R</u></p>	<p>from which new bearing trees</p> <p>A lodgepole pine, 12 ins. diam., bears N. 18½° E., 64 lks. dist., mkd. T5S R41E S33 SC BT.</p> <p>A larch, 15 ins. diam., bears N. 53¼° W., 16 lks. dist., mkd. T5S R41E S32 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base, the remains of the corner tree alongside and set a 6 ft. steel fence post alongside the stainless steel post.</p>
<p>4.25</p>	<p>S. 89° 29' 00" W., on the S. bdy. of sec. 32.</p> <p>Track road, 15 lks. wide, bears N. 40° E. and S. 40° W.; asc. gradual E. slope.</p>