


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

439.86 Point for the standard ¼ sec. cor, of sec. 33, at proportionate distances; there is no remaining evidence of the original corner. Set a stainless steel post 28 ins long, 2½ ins. diam., 24 ins. in the ground, with brass cap, from which:



A fir, 15 ins. diam., bears N.23°E., 34 lks. dist. mkd. ¼ S33 SC BT.

A lodgepole pine, 7 ins. diam., bears N.26°W., 48 lks. dist. mkd. x at breast height and BT at base.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

From this point, United States Geological Survey triangulation station "FRAZIER", as determined from a tie to the original reference monument No. 1, bears S.13°29'00"W., 17.805 chs. dist. The triangulation station has been destroyed. Reference monument No. 1, is located S.48°13'20"W., 21.74 ft from the true position, is monumented with a standard brass cap firmly set in bedrock with top marked US GEOLOGICAL SURVRY REFERENCE MARK NO 1 1964 and an arrow pointing to the true station.

Description of corner evidence found:

Found a 2½" B.L.M. brass cap, 6" above ground, with a 2' mound of stone to cap, from which:

A fir, 16" diam., bears N.23°52'E., 22.4', with a 22" x 4" blaze, scribed "¼ S33 SC BT".
A larch, 8" diam., bears N.25°52'W., 31.54', with a 6" x 3" blaze, scribed "BT at base".

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 33" diam., bears N.43°36'E., 130.56', with a 14" x 6" blaze, scribed "¼ S33 SC BT".
A tamarack, 14" diam., bears S.73°54'E., 95.00', with a 16" x 5" blaze, scribed "¼ S

UNION COUNTY
SURVEYOR

Date Received 10/18/94
Date Filed 10/23/94
By Guy To Blah
File No. 140-1994C

REGISTERED
PROFESSIONAL
LAND SURVEYOR

RE & STOLL 10/94
OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the _____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

AS

2-11

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

39.860 Point for the standard 1/4 sec. cor, of sec. 33, at proportionate distances; there is no remaining evidence of the original corner. Set a stainless steel post 28 ins long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap, from which:

A fir, 15 ins. diam., bears N.23°E., 34 lks. dist. mkd. 1/4 S33 SC BT.

A lodgepole pine, 7 ins. diam., bears N.26°W., 48 lks. dist. mkd. x at breast height and BT at base.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 6" above ground, with a 2' mound of stone to cap, from which:

A fir, 16" diam., bears N.23°52'E., 22.4', with a 22" x 4" blaze, scribed "1/4 S33 SC BT".

A larch, 8" diam., bears N.25°52'W., 31.54', with a 6" x 3" blaze, scribed "BT at base".

Description of monument and accessories I established to perpetuate the original location of this corner:

A fir, 33" diam., bears N.43°36'E., 130.56', with a 14" x 6" blaze, scribed "1/4 S33 SC BT".


A tamarack, 14" diam., bears S.73°54'E., 95.00', with a 16" x 5" blaze, scribed "1/4 S

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY

WITNESS TO MONUMENT: DAVID SUTHERLAND

BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.

BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



UNION COUNTY
CLERK
Date Received 10/28/98
Date Filed 10/31/98
by R. ROBINSON, Deputy
File No 105-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Ronald E. Stoll 9/98
OREGON
JULY 27 1983
RONALD E. STOLL
2058

Office of _____ County of _____

State of _____ I hereby certify that the within instrument was filed in this office for record on the _____ day of _____, 19__

_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of the South Boundary
 (First Standard Parallel South),
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	SC E 1/16 <u>S 33</u> 1991
	from which A larch, 18 ins. diam., bears N. 81° E., 9 lks. dist., mkd. E 1/16 S33 SC BT. A lodgepole pine, 13 ins. diam., bears N. 87° W., 44 lks. dist., mkd. E 1/16 S33 SC BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
35.50	Narrow, rocky ridge, bears N. 10° W. and S. 10° E., desc. W. slope.
39.860	Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd. <div style="text-align: center;"> SC T 5 S R 41 E <u>¼ S 33</u> 1991 </div> from which A fir, 15 ins. diam., bears N. 23° E., 34 lks. dist., mkd. ¼ S33 SC BT. A lodgepole pine, 7 ins. diam., bears N. 26° W., 48 lks. dist., mkd. X at breast height and BT at the base. Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post. From this point, United States Geological Survey triangulation station "FRAZIER," as determined from a tie to the original reference monument No. 1, bears S. 13° 29' 00" W., 17.805 chs. dist. The triangulation station has been destroyed. Reference monument No. 1, located S. 48° 13' 20" W., 21.74 ft. from the true position, is monumented with a standard brass cap firmly set in bedrock with top marked US GEOLOGICAL SURVEY REFERENCE MARK NO 1 1964 and an arrow pointing to the true station. Descend gradual W. slope.
59.790	Point for the standard W 1/16 sec. cor. of sec. 33. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 171-2013R