


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**



History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

19.930 Point for the standard E 1/16 sec. cor, of sec. 33.

Set a stainless steel post 28 ins long, 2½ ins. diam., 22 ins. in the ground, with brass cap, from which:

A larch, 18 ins. diam., bears N.81°E., 9 lks. dist. mkd. E1/16 S33 SC BT.

A lodgepole pine, 13 ins. diam., bears N.87°W., 44 lks. dist. mkd. E1/16 S33 SC BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass capped pipe, cap marked per diagram, 8" above ground, with a small mound of stone to cap, from which:

A larch, 18 ins. diam., bears N.77°11'E., 5.64' dist. mkd. E1/16 S33 SC BT.

A lodgepole pine, 13 ins. diam., bears N.86°31'W., 28.85' dist. mkd. E1/16 S33 SC BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY  
WITNESS TO MONUMENT: ERIC GREEN  
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.  
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY  
SURVEYOR  
Date Received 10/28/98  
Date Filed 10/31/98  
by R. Robinson, Deputy  
File No. 104-199BR

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR  
Ronald E. Stoll 9/98  
OREGON  
JULY 15, 1993  
RONALD E. STOLL  
2058

Office of \_\_\_\_\_ County of \_\_\_\_\_  
State of \_\_\_\_\_ I hereby certify that the within instrument was filed in this office  
for record on the \_\_\_\_ day of \_\_\_\_\_, 19\_\_

\_\_\_\_\_ by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

CE

Dependent Resurvey of the South Boundary  
(First Standard Parallel South),  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr/> <p>S. 89° 34' 30" W., on the S. bdy. of sec. 33.</p> <p>Ascend over SE. slope.</p> <p>13.425 From this point, the original closing cor. of secs. 3 and 4, T. 6 S., R. 41 E., bears North, 0.460 chs. dist., monumented with the original basalt stone, 17 x 14 x 4 ins., loosely set at the center of a stone mound with no marks, from which the remains of the original bearing trees:</p> <ul style="list-style-type: none"> <li>A root hole, bears N. 57° E., 70 lks. dist., with pine log, 30 ins. diam., alongside, with scribe mark S on upper blaze and BT on lower blaze.</li> <li>A ponderosa pine, 33 ins. diam., bears S. 85° E., 74 lks. dist., with scribe marks 41E S3 on upper blaze and BT on lower, partially healed blaze. (Record, S. 82° E.)</li> <li>A root hole, bears S. 29° W., 90 lks. dist., with pine log alongside, 25 ins. diam., with scribe marks TRS visible on upper open blaze and BT on lower open blaze.</li> </ul> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>												
	<table border="0"> <tr><td>T 5 S</td><td>R 41 E</td></tr> <tr><td>S 33</td><td></td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>T 6 S</td><td>R 41 E</td></tr> <tr><td>CC</td><td></td></tr> <tr><td>1991</td><td></td></tr> </table>	T 5 S	R 41 E	S 33		S 4	S 3	T 6 S	R 41 E	CC		1991	
T 5 S	R 41 E												
S 33													
S 4	S 3												
T 6 S	R 41 E												
CC													
1991													
	<p>from which new bearing trees</p> <ul style="list-style-type: none"> <li>A lodgepole pine, 9 ins. diam., bears S. 51° E., 11 lks. dist., mkd. T6S R41E S3 CC BT.</li> <li>A ponderosa pine, 13 ins. diam., bears S. 16¼° W., 56 lks. dist., mkd. T6S R41E S4 CC BT.</li> </ul> <p>Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.</p> <p>Continue to ascend SE. slope.</p> <p>14.50 Top of ascent; along nearly level ridgetop.</p> <p>19.930 Point for the standard E 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>												

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>NA Gilman</i>
File No.	172-2013R

Dependent Resurvey of the South Boundary  
 (First Standard Parallel South),  
 T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">SC                      E 1/16  <u>S 33</u>                      1991</p> <p>from which</p> <p>A larch, 18 ins. diam., bears N. 81° E., 9 lks. dist., mkd. E 1/16 S33 SC BT.</p> <p>A lodgepole pine, 13 ins. diam., bears N. 87° W., 44 lks. dist., mkd. E 1/16 S33 SC BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
35.50	<p>Narrow, rocky ridge, bears N. 10° W. and S. 10° E.; desc. W. slope.</p>
39.860	<p>Point for the standard ¼ sec. cor. of sec. 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SC                      T 5 S R 41 E  <u>¼ S 33</u>                      1991</p> <p>from which</p> <p>A fir, 15 ins. diam., bears N. 23° E., 34 lks. dist., mkd. ¼ S33 SC BT.</p> <p>A lodgepole pine, 7 ins. diam., bears N. 26° W., 48 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p> <p>From this point, United States Geological Survey triangulation station "FRAZIER," as determined from a tie to the original reference monument No. 1, bears S. 13° 29' 00" W., 17.805 chs. dist. The triangulation station has been destroyed. Reference monument No. 1, located S. 48° 13' 20" W., 21.74 ft. from the true position, is monumented with a standard brass cap firmly set in bedrock with top marked US GEOLOGICAL SURVEY REFERENCE MARK NO 1 1964 and an arrow pointing to the true station.</p>
59.790	<p>Descend gradual W. slope.</p> <p>Point for the standard W 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>N.L. Miller</i>
File No.	172-2013R